

## 20 Amp, 3ØY 120/208, 277/480 and 347/600 Volts AC 4 Pole, 4 Wire, Non-Grounding

**IP20**  
SUITABILITY



20A 3ØY 120/208V AC  
NEMA L18-20P  
2 HP

20A 277/480V AC  
NEMA L19-20P  
5 HP

20A 347/600V AC  
NEMA L20-20P

### Plugs

| Description            | Cord Dia.              | Catalog Number                               |
|------------------------|------------------------|----------------------------------------------|
| Black and white nylon. | .350"-1.150"<br>(9-29) | <b>HBL2441</b> <b>HBL2451</b> <b>HBL2461</b> |

Note: See page B-52 for accessories.




**HBL2441**

### Flanged Inlets

| Description               | Catalog Number                               |
|---------------------------|----------------------------------------------|
| Nylon casing, back wired. | <b>HBL2445</b> <b>HBL2455</b> <b>HBL2465</b> |

Note: See page B-52 for accessories.



**HBL2445**

**IP20**  
SUITABILITY



20A 3ØY 120/208V AC  
NEMA L18-20R  
2 HP

20A 277/480V AC  
NEMA L19-20R  
5 HP

20A 347/600V AC  
NEMA L20-20R

### Connector Bodies

| Description            | Cord Dia.              | Catalog Number                               |
|------------------------|------------------------|----------------------------------------------|
| Black and white nylon. | .350"-1.150"<br>(9-29) | <b>HBL2443</b> <b>HBL2453</b> <b>HBL2463</b> |

Note: See page B-52 for accessories.




**HBL2443**

### Single Flush Receptacles

| Description                               | Catalog Number                               |
|-------------------------------------------|----------------------------------------------|
| Black nylon face,<br>back and side wired. | <b>HBL2440</b> <b>HBL2450</b> <b>HBL2460</b> |

Note: See page B-52 for accessories.



**HBL2440**

### Flanged Receptacles

| Description               | Catalog Number                               |
|---------------------------|----------------------------------------------|
| Nylon casing, back wired. | <b>HBL2446</b> <b>HBL2456</b> <b>HBL2466</b> |

Note: See page B-52 for accessories.


See page B-69 for technical information.

See page B-39 for switched enclosure.

See page B-42 for Add-A-Shroud® kit. For use with connector bodies.

Only receptacles and plugs up to 480V AC are HP rated.

HP ratings are AC only.



**HBL2446**

Dimensions in Inches (mm)