

## **Heavy Duty Panel Mount**

## 10A 250V AC 20A 125V AC Horsepower Rated 11/2 HP, 125-250V AC

Description		Terminal	Catalog Number
Double pole/ single throw.	.75" (19.1) Spade Terminal Shown	Screw Spade	HBL21 HBL21SP
Double pole/ single throw.	.75" (19.1)	Screw Spade	HBL22 HBL22SP
Double pole/ double throw 3-position center OFF.	OFF   .80" (20.3)   .30" (33.0)   .30" (19.1)   .5crew Terminal Shown	Screw Spade	HBL223 HBL223SP
Double pole/ double throw 3-position center OFF momentary.	OFF	Screw Spade	HBL223MM HBL223SPMM
Silicone rubber boot.		Screw Spade	SSB1



HBL21

**HBL223** 



Note: All threaded stems 15/2 in.-32 thread.

See AA-33 for additional information on 12V DC tapered handle switches.

## 4A 250V 8A 125V 10A 120V AC 1/3 HP 120V AC

Description		Terminal	Catalog Number
Single pole/ single throw.	0.41" (10.4) Black Nylon Plunger 1.58" 0.15" (12.5) (12.5) (12.5) (13.5) (15.4) (152.4) (152.4) (152.4) (16.5) (16.5)	#18 Std. AWG Copper Wire Leads 105° C Black.	HBL11PBWL

Note: 15/32 in.-32 thread, keyway .080 x .035.



**HBL11PBWL**