





**HBL7777A** 

HBL9420

HBL7774WO

### For Receptacles with Face Diameters of 2.28–2.44 in. (57.9–62.0)

Description	Catalog Number
Thermoplastic, 2-gang, wet and damp locations with cover "closed", gray.	HBL7777A <b>▲</b>
Thermoplastic, 2-gang, wet and damp locations with cover "closed", yellow.	HBL77CM77A▲

### For Receptacles with Face Diameters of 2.09-2.13 in. (53.1-54.1)


Description	Catalog Number
Cast aluminum, wet locations only when cover "closed" and damp locations.	HBL9420
Cast aluminum, no lift cover. NOT weatherproof.	HBL9419

# For 50A Twist-Lock® Single Receptacles

Description	Catalog Number
Thermoplastic, wet and damp locations with cover "open", gray.	HBL7774WO*
Thermoplastic, wet and damp locations with cover "open", yellow.	HBL77CM74WO*
Cast aluminum, wet locations only when cover "closed" and damp locations.	HBL7770
Galvanized Steel, fits 4" square or 2-gang box.	HBL50SC**
Stainless steel, single gang, wallplate. NOT weatherproof.	SS750 <sup>4</sup>

## For 30A, 4 Wire Hubbellock® Receptacles

Tor cort, Trino Habbellook Hocoptacios	
Description	Catalog Number
Thermoplastic, wet and damp locations with cover "open", gray.	HBL7428WOG*
Thermoplastic, wet and damp locations with cover "open", yellow.	HBL7428WOY*
Thermoplastic, wet and damp locations with cover "open", red.	HBL7428WOR*
Cast aluminum, wet locations only when cover "closed" and damp locations, lift cover plate.	HBL20405
Cast aluminum, wet locations only when cover "closed" and damp locations, red finish.	HBL20446
Cast aluminum, no lift cover. NOT weatherproof.	HBL20406



\*The "CS" versions of 50A Twist-Lock® will only fit these plates.



Note: All weatherproof plates are UL Listed for WET LOCATIONS WITH COVER CLOSED, for intermittent use in wet locations or use in damp locations. Those with suffix "WO" are listed for WET LOCATIONS with cover open in continuous use. All plates are gasketed and self-closing.



#### **Accessories**

Description	Catalog Number
Sub-plate for mounting and weatherproofing flanged devices with mounting centers of 1.76", 1.94" or 2.13" such as HBL7556, HBL4716, etc. when used with a HBL7420 or HBL7425WOA type weatherproof plate.	7452°
Adapter plate for mounting HBL7423WO, HBL7424WO, HBL7425WOA or HBL7420 plates to standard boxes.	HBL7349 <sup>•</sup>


Note: \*Not UL Listed.




HBL20405



**HBL7349** 





Typical Plate, 1-Gang

Dimensions in Inches (mm)