

# Cable, Cord and Hose Reels



HBL50162LED

## Industrial Lighted Cord Reels, 50 Ft. (15.2m) - 16/3 AWG SJEO Cable



| Cord End                       | Watts (Max) | Amps | Volts AC | Weight Lbs. (kg) | Catalog Number     |
|--------------------------------|-------------|------|----------|------------------|--------------------|
| LED hand lamp, with end light. | 8 + 1       | 0.07 | 120      | 21 (9.5)         | <b>HBL50162LED</b> |
| Fluorescent hand lamp.         | 13          | 0.3  | 120      | 21 (9.5)         | <b>HBL50162FL</b>  |
| Incandescent hand lamp.        | 100         | 0.8  | 125      | 21 (9.5)         | <b>HBL50163IN</b>  |

Note: Supplied with 5 ft. power supply cord with HBL5266C, 15A straight blade plug.

## Accessories



HBL16BS

| Description                         | Watts (Max) | Amps | Volts AC | Weight Lbs. (kg) | Catalog Number    |
|-------------------------------------|-------------|------|----------|------------------|-------------------|
| Replacement stop.                   | —           | —    | —        | .2 (.09)         | <b>HBL16BS</b>    |
| Replacement LED hand lamp.          | 8 + 1       | 0.07 | 120      | 1 (.5)           | <b>HBL16LEDR*</b> |
| Replacement fluorescent hand lamp.  | 13          | 0.3  | 120      | 1 (.5)           | <b>HBL16FLR</b>   |
| Replacement incandescent hand lamp. | 100         | 0.8  | 125      | 1 (.5)           | <b>HBL16INR</b>   |

Note: \*ETL Listed by INTERTEK.



HBL40182LED



HBL50162FL



HBL50163IN

## Commercial Lighted Cord Reels



| Description                                                                          | Cable Feet (m) | Cable Type  | Watts (Max) | Amps | Volts AC | Weight Lbs. (kg) | Catalog Number       |
|--------------------------------------------------------------------------------------|----------------|-------------|-------------|------|----------|------------------|----------------------|
| Reel with LED hand lamp, with flashlight end, white                                  | 40 (12.2)      | #18/2 SJTOW | 8 + 1       | 0.65 | 125      | 8.2 (3.7)        | <b>HBL40182LED</b>   |
| Reel with non-metallic incandescent hand lamp and automatic shut off switch, yellow. | 25 (7.6)       | #16/3 SJT   | 75          | 0.6  | 125      | 9.0 (4.1)        | <b>HBL40182AFL**</b> |
| Reel with metallic incandescent hand lamp with receptacle, yellow.                   | 25 (7.6)       | #14/3 SJT   | 1,625       | 13   | 125      | 9.5 (4.3)        | <b>HBL40182AFL**</b> |
| Reel with fluorescent hand lamp and automatic shut off switch, white.                | 40 (12.2)      | #18/2 SJTOW | 13          | 0.3  | 120      | 8.2 (3.7)        | <b>HBL40163FL</b>    |
| Reel with fluorescent hand lamp and in-line receptacle, white.                       | 40 (12.2)      | #16/3 SJT   | 1,200       | 10   | 120      | 9.0 (4.1)        | <b>HBL40163FL</b>    |

Note: \*\*Allows the electrical cord reel installation to conform to Article 511 of the National Electric Code concerning installation of electrical devices in commercial garages, repair facilities and storage locations by positioning the switch above the defined area where hazardous fumes may collect.



HBL40163FL



INTERTEK and the Intertek logo are registered trademarks of Intertek Group plc.