




## Traditional Flush 2X2 FRPT 3 Inch Core Hole Units, for Use In Concrete Floors

### 2X2 Flush FRPT, One-Piece Units (PT2X2FIT)

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
2X2 Poke-Through Non-metallic Cover	Black/Aluminum Black/Aluminum Black Gray Black Gray	<b>PT2X2ALU3</b> <b>PT2X2IGALU3</b> <b>PT2X2BL</b> <b>PT2X2GY</b> <b>PT2X2IGBL*</b> <b>PT2X2IGGY*</b>	2X2 Poke-Through	Black/Brass Brass Finish/Brass Black/Brass Brass Finish/Brass	<b>PT2X2BRS3</b> <b>PT2X2BRS</b> <b>PT2X2IGBRS3*</b> <b>PT2X2IGBRS*</b>
<ul style="list-style-type: none"> <li>Pre-wired 20A Style Line® decorator duplex receptacle and (2) Category 6 data jacks</li> <li>Painted or brushed aluminum flange</li> <li>Approved for use in the City of Chicago</li> </ul>			<ul style="list-style-type: none"> <li>Pre-wired 20A Style Line® decorator duplex receptacle and (2) Category 6 data jacks</li> <li>Solid brass flange</li> <li>Approved for use in the City of Chicago</li> </ul>		

Note: \*Includes pre-wired 20A isolated ground Style Line® decorator duplex receptacle.



### 2X2 Flush FRPT, Two-Piece Units

Description	Catalog Number
Multi-Channel Through-Floor Fitting with (1) ¼ in. EMT stem with junction box for power and (2) ½ in. EMT stems for low voltage.	<b>PT2X2FIT</b>
	<p>Specifications:</p> <ul style="list-style-type: none"> <li>1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design)</li> <li>For 2¼ in. to 7 in. floor thickness</li> <li>UL installation spacing – minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area</li> <li>Approved for use in the City of Chicago</li> </ul>

### Service Fittings

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
2X2 Service Fitting Non-metallic Cover/ Aluminum Flange	Black/Aluminum Black Gray	<b>PT2X2SFALU3</b> <b>PT2X2SFBL</b> <b>PT2X2SFGY</b>	2X2 Service Fitting Non-metallic Cover/ Brass Flange	Black/Brass Brass Finish/Brass	<b>PT2X2SFBR3</b> <b>PT2X2SFBR3</b>
<ul style="list-style-type: none"> <li>Pre-wired 20A Style Line® decorator duplex receptacle and (2) Category 6 data jacks</li> <li>Painted or brushed aluminum flange</li> </ul>			<ul style="list-style-type: none"> <li>Pre-wired 20A Style Line® decorator duplex receptacle and (2) Category 6 data jacks</li> <li>Solid brass flange</li> </ul>		

### Accessories

Description	Color/Material	Catalog Number	Description	Color/Material	Catalog Number
Non-metallic Replacement Covers	Brass Finish Black Gray	<b>PT2X2CBRS</b> <b>PT2X2CBL</b> <b>PT2X2CGY</b>	<b>Closure Plug</b> Textured aluminum plug seals 3 in. core hole when FRPT is no longer required and is removed. Maintains the floor's 1 – 4 hour fire rating. UL Listed and CSA Certified.	Gray	<b>FRP250</b>
					

Note: See page Q-43 for technical information.