

Straight Blade Devices

Miscellaneous and Combination Receptacles

2 Pole, 3 Wire Grounding



15A 125V
NEMA 5-15R
UL CSA
0.5 HP



HBL5236



HBL5235













Miscellaneous Receptacles

Description	Catalog Number
Receptacle, display type, brown phenolic with .060 in. brass plate and blank flush plug.	HBL5236
Replacement receptacle for HBL5236.	HBL5236M2
Replacement threaded plug for HBL5236.	HBL5236PLUG*
Receptacle, wooden floors, brown phenolic with .060 in. brass plate, blank flush plug and box.	HBL6236
Receptacle, clock hanger, brown with stainless steel plate.	HBL5235
Four outlet cluster, brown phenolic, steel cover, swivel hook. Cord grip range .296-.562 in. (7.5-14.3) cord not supplied.	HBL9259*

Note: *Not UL Listed or CSA certified.

Special Combination Duplex Receptacles


Description	Catalog Number
15A, 125V 	Brown RTP, 1 feed, 1 return, back/side wired HBL4792
15A, 125V 	Brown RTP, 2 feeds, 1 return, side wired HBL4794
15A, 125V 	Brown RTP, 2 feeds, 2 returns, side wired HBL4795
15A, 250V 	Brown nylon face, 2 circuit, back and side wired HBL5292
15A, 125V 	Ivory nylon face, 2 circuit, back and side wired HBL5292I
20A, 250V 	Brown nylon face, 2 circuit, back and side wired HBL5492
20A, 125V 	Ivory nylon face, 2 circuit, back and side wired HBL5492I
15A, 125V 	Brown RTP, 2 feeds, 1 return, common ground HBL7371
10A, 250V 15A, 125V 	Brown nylon, side and back wired HBL5392
20A, 125V 	

Note: This device will only accept 20A grounding plugs.


Note: RTP is an abbreviation for reinforced thermoplastic polyester.

*Not UL Listed or CSA certified.

See page A-47 for accessories.



HBL9259



HBL5292

Dimensions in Inches (mm)