



YA32L2TC38FX

by Burndy
Catalog ID: YA32L2TC38FX

Prop 65 Notice

Copper Compression Lug, 2 Hole w/ Inspection Window, 313.1 kcmil, 3/8" Stud, 1" Stud Hole Spacing, Short Barrel, Tin Plated

Product Details

General

| | |
|--------------------------------------|-----------------------------|
| Color Code | Red |
| Connector Type | Terminal |
| Die Index | 18;324 |
| Feature - Barrel Style | Chamfered |
| Feature - Barrel Type | Standard |
| Material | Copper |
| Physical Attribute - Number of Holes | 2 |
| Physical Attribute - Tongue Type | Standard |
| Plated | Y |
| Plating Type | Tin |
| Trade Name | HYLUG™ |
| Type | Standard Barrel, Tin Plated |
| UPC | 781810037195 |
| UPC 12 Digit | 7818100371955 |

Dimensions

| | |
|-----------------------------------|-----------|
| Dimension - B Length fraction | 1-3/16 in |
| Dimension - B Length inch | 1.19 in |
| Dimension - Bolt Hole Size inch | 0.39 in |
| Dimension - Bolt Size fraction | 3/8 |
| Dimension - Hole Size inch | 0.40 in |
| Dimension - Hole Size mm | 10 mm |
| Dimension - L Length Overall mm | 94 mm |
| Dimension - Length Overall inch | 3.69 in |
| Dimension - N inch | 0.41 in |
| Dimension - Outside Diameter inch | 0.95 in |
| Dimension - Pad Width inch | 1.40 in |
| Dimension - Strip Length inch | 1-1/4 |
| Dimension - Z inch | 0.65 in |
| Physical Attribute - Tongue Angle | Straight |

Electrical Ratings

| | |
|--------------------------|-------|
| Rating - KVA | 35 kV |
| Rating - Minimum Voltage | 600 |
| Voltage - Maximum | 35000 |

Conductor Related

| | |
|--------------------------------|---------------------|
| Conductor - Copper DLO Size | 313.1 (775/#24) DLO |
| Conductor - Copper Flex G Size | 300 kcmil |
| Conductor - Copper Flex H Size | 300 kcmil |
| Conductor - Copper Flex I Size | 300 kcmil |
| Conductor - Copper Flex K Size | 300 kcmil |
| Conductor - Copper Flex M Size | 300 kcmil |
| Conductor - Material | Copper |

Certifications and Compliance

| | |
|------------------------------------|-----|
| Certification - CSA Approved | Yes |
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

Logistics

| | |
|-----------------------|----|
| Minimum Pack Quantity | 25 |
|-----------------------|----|

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)