Fire-Rated Poke-Throughs







SystemOne Recessed 10 Inch Core Hole Kits, for Use In Concrete Floors

10 Inch Fire-Rated Poke-Through
Hubbell SystemOne 10 Inch Recessed Floor Fitting with Installation Cover

Catalog Number S1R10PTFIT

Approved for use in the City of Chicago with EMT and full blank bottom feed plates.

Note: See page Q-36 for technical information.

10 Inch Fire-Rated Poke-Through Kits

Kits include:
 (1) Hubbell SystemOne 10 inch recessed floor fitting (S1R10PTFIT)

 (2) Hubbell SystemOne 10 inch perimeter device mounting brackets (S1R10PSPREPBRKT)

• (4) Hubbell SystemOne 10 inch bottom center pass through plate (S1R10CBFPT)


• (3) Hubbell SystemOne 10 inch bottom perimeter blank plate (S1R10PBFBLANK)

(3) Hubbell Systemone To Inch bottom perimeter blank plate (5 1R TOPBEBLANK)

(1) Hubbell SystemOne 10 inch bottom perimeter % inch plate (S1R10PBF075)
(1) Hubbell SystemOne 10 inch perimeter divider (S1R10PERIMDIV)

• (1) Hubbell SystemOne 10 inch center divider (S1R10CENTERDIV)

• (1) Hubbell SystemOne 10 inch flange and universal cover assembly (S1R10CVRxx)





S1R10PTFIT


S1R10PTBRS

Pre-Wired 10 Inch Fire-Rated Poke-Through Kits

Kits include:

- (1) Hubbell SystemOne 10 inch recessed floor fitting (S1R10PTFIT)
- (2) 20A pre-wired receptacle sub-plates with 24 inch wire leads (S1R10PSPZ)
- (2) Hubbell SystemOne 10 inch perimeter device mounting brackets (S1R10PSPREPBRKT)
- (4) Hubbell SystemOne 10 inch bottom center pass through plate (S1R10CBFPT)
- (3) Hubbell SystemOne 10 inch bottom perimeter blank plate (S1R10PBFBLANK)
- (1) Hubbell SystemOne 10 inch bottom perimeter ¾ inch plate (S1R10PBF075)
- (1) Hubbell SystemOne 10 inch perimeter divider (S1R10PERIMDIV)
- (1) Hubbell SystemOne 10 inch center divider (S1R10CENTERDIV)
- (1) Hubbell SystemOne 10 inch flange and universal cover assembly (S1R10CVRxx)

Receptacles feature single circuit wiring





S1R10PTZBLK



Note: xx indicates finish options.

Recessed 10 Inch Covers

The 10 inch FRPT cover assembly unit includes solid cast aluminum construction and mounting hardware. Covers are recessed and available in a number of durable, yet beautiful finishes to match any décor. The flange height of 0.16 inch exceeds ADA requirement and suitable for use on any floor finish. All covers are UL514A, scrubwater compliant.















10 Inch Fire-Rated Poke-Through Covers

Finish	Recessed Cover	TR Recessed Cover*	Furniture Feed Cover**
	Catalog Number	Catalog Number	Catalog Number
Brushed Aluminum	S1R10CVRALU	S1R10CVRTRALU	S1R10FFCVRALU
Black Powder Coat	S1R10CVRBLK	S1R10CVRTRBLK	S1R10FFCVRBLK
Brushed Brass Plated	S1R10CVRBRS	S1R10CVRTRBRS	S1R10FFCVRBRS
Antique Bronze Plated	S1R10CVRBRZ	S1R10CVRTRBRZ	S1R10FFCVRBRZ
Gray Powder Coat	S1R10CVRGRY	S1R10CVRTRGRY	S1R10FFCVRGRY
Satin Nickel Plated	S1R10CVRNKL	S1R10CVRTRNKL	S1R10FFCVRNKL

Note: COVER LOAD RATING: 1,000 lbs with 2x safety factor. Load applied through a 3" (76mm) dia. mandrel at the center of the cover. Rated for static loads only.

^{*}Tamper-resistant covers ship with (1) S1RTR10BIT Torx-T10 bit.

^{**(2) 1&}quot; NPT plugs for power with (2) 1" to 3/4" reducers and (2) 2" NPT plugs for Low Voltage.