

# Aluminum Raceway



## Aluminum PlugTrak® Series

Available in Standard, Isolated Ground (IG), Tamper-Resistant (TR) and USB (U) versions.



USB



Tamper-Resistant

|        | Amp Circuits  | Single Recept. | USB Ports | Receptacle Spacing (in.) | Catalog Number         |
|--------|---------------|----------------|-----------|--------------------------|------------------------|
| 3 Foot | 15 Single     | 6              | —         | 6                        | <b>HBLALU20GB306</b>   |
|        | 15 IG/Single  | 6              | —         | 6                        | <b>HBLALU20IG306</b>   |
|        | 15 TR/Single  | 6              | —         | 6                        | <b>HBLALU20GB306TR</b> |
|        | 15 USB/Single | 2              | 2         | 12                       | <b>HBLALU20GB312U</b>  |
|        | 20 Single     | 6              | —         | 6                        | <b>HBLALU24GB306</b>   |
|        | 20 IG/Single  | 6              | —         | 6                        | <b>HBLALU24IG306</b>   |
|        | 20 TR/Single  | 6              | —         | 6                        | <b>HBLALU24GB306TR</b> |
| 5 Foot | 15 Single     | 10             | —         | 6                        | <b>HBLALU20GB506</b>   |
|        | 15 Single     | 5              | —         | 12                       | <b>HBLALU20GB512</b>   |
|        | 15 IG/Single  | 10             | —         | 6                        | <b>HBLALU20IG506</b>   |
|        | 15 TR/Single  | 5              | —         | 12                       | <b>HBLALU20GB512TR</b> |
|        | 20 Single     | 10             | —         | 6                        | <b>HBLALU24GB506</b>   |
|        | 20 Single     | 5              | —         | 12                       | <b>HBLALU24GB512</b>   |
|        | 20 IG/Single  | 10             | —         | 6                        | <b>HBLALU24IG506</b>   |
| 6 Foot | 20 TR/Single  | 5              | —         | 12                       | <b>HBLALU24GB512TR</b> |
|        | 15 Single     | 12             | —         | 6                        | <b>HBLALU20GB606</b>   |
|        | 15 Single     | 6              | —         | 12                       | <b>HBLALU20GB612</b>   |
|        | 15 Single     | 4              | —         | 18                       | <b>HBLALU20GB618</b>   |
|        | 15 Two        | 12             | —         | 6                        | <b>HBLALU20GBA606</b>  |
|        | 15 Two        | 6              | —         | 12                       | <b>HBLALU20GBA612</b>  |
|        | 15 Two        | 4              | —         | 18                       | <b>HBLALU20GBA618</b>  |
|        | 15 IG/Single  | 12             | —         | 6                        | <b>HBLALU20IG606</b>   |
|        | 15 USB/Single | 4              | 4         | 12                       | <b>HBLALU20GB612U</b>  |
|        | 20 Single     | 12             | —         | 6                        | <b>HBLALU24GB606</b>   |
|        | 20 Single     | 6              | —         | 12                       | <b>HBLALU24GB612</b>   |
|        | 20 Single     | 4              | —         | 18                       | <b>HBLALU24GB618</b>   |
|        | 20 Two        | 12             | —         | 6                        | <b>HBLALU24GBA606</b>  |
|        | 20 Two        | 6              | —         | 12                       | <b>HBLALU24GBA612</b>  |
|        | 20 Two        | 4              | —         | 18                       | <b>HBLALU24GBA618</b>  |
|        | 20 IG/Single  | 12             | —         | 6                        | <b>HBLALU24IG606</b>   |

|                 | Description                | Catalog Number     |
|-----------------|----------------------------|--------------------|
| Device Boxes    | Standard 1-Gang Device Box | <b>HBLALU2047</b>  |
|                 | Deep 1-Gang Device Box     | <b>HBLALU2044</b>  |
|                 | Standard 2-Gang Device Box | <b>HBLALU20472</b> |
|                 | Deep 2-Gang Device Box     | <b>HBLALU20442</b> |
|                 | Round Box                  | <b>HBLALU2038</b>  |
|                 |                            |                    |
| Elbows and Tees | External Elbow             | <b>HBLALU2018</b>  |
|                 | Internal Elbow             | <b>HBLALU2017</b>  |
|                 | Flat Elbow                 | <b>HBLALU2011</b>  |
|                 | Tee                        | <b>HBLALU2015</b>  |
| Fittings        | Cover Clip                 | <b>HBLALU2006</b>  |
|                 | Supporting Clip            | <b>HBLALU2003</b>  |
|                 | Coupling                   | <b>HBLALU2001</b>  |
|                 | Entrance End Fitting       | <b>HBLALU2010A</b> |
|                 | In-Line Switch Fitting     | <b>HBLALU2040A</b> |
|                 | Blank End Fitting          | <b>HBLALU2010B</b> |

Note: See pages T-34 and T-35 for additional information.

Note: IG = Isolated Ground, TR = Tamper-Resistant and U = USB.  
Hubbell Aluminum PlugTrak is supplied with two HBLALU2010B blank end fittings and one HBLALU2001 coupling.

Dimensions in Inches (mm)