



15A 125V
NEMA 5-15P
UL CSA




20A 125V
NEMA 5-20P
UL CSA


Flanged Inlets

Description	Catalog Number	
Nylon casing, back wired.	HBL5278C	HBL5378C
Weatherproof, gray, with lift cover and multiple drive screws.	HBL61CM64	—
Weatherproof, black, with lift cover and boot, multiple drive screws.	HBL61CM64BK	—
Stainless steel flange, phenolic body, miniature style, for molded on connectors only, multiple drive screws.	HBL5240*	—

Note: *Specially designed to accept "molded-on" connector bodies. Catalog number HBL5240 will not accept re-wireable size connector bodies listed in this catalog or molded connectors having a "rejection obstruction" as required by Underwriters Laboratories Inc. standard #817 cord sets and power supply cords" effective 7/1/81.
See pages A-47 and A-48 for accessories.



HBL5278C



HBL61CM64



15A 125V
NEMA 5-15R
UL CSA
0.5 HP




20A 125V
NEMA 5-20R
UL CSA
1 HP


Flanged Receptacles

Description	Catalog Number	
Nylon casing, back wired.	HBL5279C	HBL5379C
Stainless steel flange, phenolic body, covered terminals, multiple drive screws.	HBL5279	—
Stainless steel flange, brown phenolic (mounting screws packed separately).	HBL5256	—
Weatherproof, gray nylon, with lift cover and boot, multiple drive screws.	—	HBL61CM65**


Note: **Not CSA Certified.
See pages A-47 and A-48 for accessories.



HBL5279C



HBL5256



HBL61CM65

Dimensions in Inches (mm)