

YS28T

by Burndy
Catalog ID: YS28T

Prop 65 Notice

Copper Compression Splice, 4/0 AWG, 2.67" Splice Length, Short Barrel, Tapered End, Tin Plated.

Features: Seamless Types YS-T High Conductivity Copper Electro-Tin Plated Compression HYLINK High-Voltage Splices With Standard Barrel And Tapered Ends Are Ideally Suited For Higher Voltage Applications From 5KV Through 35 KV, Tapered Connector Ends Per EEI Standard TD160, Suitable For Use On Voltages 5KV Through 35KV To Aid In Preventing Corona Emission And Simplify Taping Thus Lowering Installed Cost, Type YS-T Four Center Wire Stops: Provides A Center Wire Stop For Proper Conductor Insertion, Tools, Die Nest Catalog Number, Die Indentor Catalog Number: Y35, Y39, Y750 Tool, U28D-1 Die Nest, Y34PR Indentor, Y35P3 Adaptor, Installation Tool: Y34B, Y34PR Indentor, B28D Die Nest, Tapered End: Yes, Oil Stop: No, Die Index: 15 Element A, Conductor Type: Commercial Stranded Copper, Tools, Die Set Catalog Number, And (number Of Crimps): PAT750 Tool, U28RT Die, (2), Y35, Y39, Y46, Y750 Tool, U28RT Die With PUADP-1 Adapter, Wire Strip Length: 1-3/16 IN



Product Details

General

Application	For Higher Voltage Applications From 5 KV Through 35 KV
Sub Brand	HYLINK
Type	YS-T, High Voltage, Standard Barrel
UPC	781810001226

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)