

Straight Blade Devices

20A, 125V, 2 Pole, 3 Wire Grounding

Hubbell-PRO Heavy Duty Hospital Grade

Receptacles

Features

- Triple wipe contacts
- High impact resistant face with circuit I.D. marking area
- Steel mounting strap

Ordering Information

Description	Device Color	UPC Number	Catalog Number
Hospital grade, smooth face, back and side wired	Brown	783585197333	8300

Listings

Certified to CSA, C22.2, No. 42 File 285
UL Listed to UL498 File No. E2186
Fed. Spec. W-C-596
NEMA® WD-6 Compliant



Specifications

Power Contacts	Brass
Clamping Plate	Plated steel
Mounting Strap	Galvalized steel
Automatic Self-grounding Staple	Stainless steel
Face	Nylon
Base	PBT
Mounting Screws	Zinc plated steel
Ground Contacts	Brass

Performance

Electrical	
Current Interrupting	Certified for current interrupting at full rated current
Dielectric Voltage	Withstands 2,000V minimum
Mechanical	
Product Identification	Ratings are a permanent part of the device
Terminal Accommodation	#12-#10 AWG stranded or solid copper wire only
Terminal Identification	Terminals identified in accordance with UL 498 and CSA
Environmental	
Flammability	UL 94V-2
Operating Temperature	Maximum continuous 75°C; minimum -40°C (w/o impact)

HUBBELL



Complementary Products

Wallplate or Weatherproof Cover	Duplex Opening
---------------------------------	----------------

Online Resources

Customer Sales Drawings
eCatalog
Installation Instructions

