

Project:		
Fixture Type:		
Location:		
Contact:		

## LED Linear Cloud

Ceiling mounted • Damp location listed PROGRESS LED





## **Description:**

LED Linear Soft Cloud features an LED light source, offering both form and function with energy- and cost-savings benefits. The LED Linear Cloud can be used in kitchens, basements, garages and many other utility areas. It has a white contoured shallow acrylic cloud lens. The LED Linear Soft Cloud is a ceiling mount fixture that delivers 2,908 lumens, is 90 CRI and with 3000K color temperature. Acrylic diffuser gives even light distribution. ENERGY STAR certified, Title 24 compliant, Damp location listed. Flicker-free dimming to 10% brightness with most Forward Phase (Triac) dimmers.

### **Specifications:**

- White (-30) (painted)
- · Steel construction
- · LED Linear Cloud
- · Features an LED light source, offering both form and function with energy- and costsavings benefits
- The LED Linear Cloud can be used in kitchens, basements, garages and many other utility areas
- · White contoured shallow acrylic cloud lens
- · The LED Linear Cloud is a ceiling mount fixture
- · 40W LED module offers 76 lumens per watt
- · 2,908 lumens, 90 CRI and 3000K color temperature
- · Acrylic diffuser for even light distribution
- Measures 3 1/4" H x 10 1/4" W x 51" L
- · Damp location listed
- · Mounting for outlet box included
- Canopy covers standard 4" hexagonal outlet box
- 5-year warranty
- Dimmable to 10% brightness (See Dimming Notes)
- ENERGY STAR® qualified
- Meets California Title 24 high efficacy requirements

#### Performance:

Number of Modules	1	
Input Power	40w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW	2989/76 (LM-79)	
ССТ	3000 K	
CRI	90 CRI	
Life (hours)	52,000 (L70/TM-21)	
EMI/RFI		
Min. Start Temp	-30 ℃	
Max. Operating Temp		
Warranty	5 year warranty	
Labels	cETLus Damp location listed	
	ENERGY STAR® qualified	
	Meets California Title 24 high efficacy	
requirements		

## P7279-3030K9

#### Images:



#### **Dimensions:**

10-1/4" Height: 3-1/4"



# LED Linear Cloud

Ceiling mounted • Damp location listed PROGRESS LED



## P7279-3030K9

## **Dimming Notes:**

P7279 is designed to be compatible with many Triac/Forward Phase controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron DVCL-153P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.