Fire-Rated Poke-Throughs



Painted Pedestal FRPT 2 and 3 Inch Core Hole Units, for Use In Concrete Floors

3 Inch Core Hole, Two-Piece Unit

2 Inch Core Hole, Two-Piece Unit

·	,					
Description	Catalog Number	Description	Catalog Number			
Large Capacity Multi-Service Pedestal Through-Floor Fitting with (1) 11/4 in. EMT stem for low voltage and (1) 1/2 in. EMT stem for power applications.	PT7XC	Multi-Service Pedestal Through-Floor Fitting with (1) % in. EMT stem for low voltage and (1) ½ in. EMT stem for power applications.	PT27A			
 Specifications: 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design) For 2¼ in. to 7 in. floor thickness Approved for use in the City of Chicago 		 Specifications: 1 - 4 hour fire rating (1 - 3 hour for steel floor units and concrete topping, D900 Series Design) For 2¼ in. to 7 in. floor thickness Approved for use in the City of Chicago 				

Note: See page Q-45 for technical information.

Pedestal Service Fittings (Order 1 plate per gang)

Description	Color/Material	Catalog Number	Description	Color	Catalog Number	Description	Color	Catalog Number
2-Gang	Alum. Finish Black Gray	FR280ALA FR280BKA FR280GYA	4-Gang	Black Gray	FR480BKA FR480GYA	6-Gang	Black Gray	FR680BKA FR680GYA
Use with PT27A only.		Use with P	Use with PT27A or PT7XC.			Use with PT27A or PT7XC.		
		1	[* *]		[.0	8 D, .	(B) (SSSS)	
FR280BKA				FR4	80GYA		FR68	0BKA

- Painted aluminum housing with low voltage barrier(s); plates and devices sold separately
- For additional barriers, use FRBR1, see page Q-33.
- UL Listed and CSA Certified

Note: See page Q-45 for technical information.

Pedestal Face Plates (Order 1 plate per gang)

Description	Color/Material	Catalog Number		Description	Color/Material	Catalog Number	
Duplex	Black Gray	SS2309DBKA SS2309DGYA	.00.	Furniture feed (¾ in. KO)	Alum. Finish Black Gray	SS2309FALA SS2309FBKA SS2309FGYA	.0,
Style Line®/ GFCI	Black Gray	SS2309SLBKA SS2309SLGYA		Furniture feed (1 in. KO)	Black Gray	SS2309F1BKA SS2309F1GYA	.0.
Single receptacle (1.39 in. OD)	Black Gray	SS2309SBKA SS2309SGYA	.⁺•.	Bushed data opening (1 in. ID)	Black Gray	SS2309TBKA SS2309TGYA	*
Blank	Alum. Finish Black Gray	SS2309BALA SS2309BBKA SS2309BGYA		Painted alum UL Listed and			