



BURNDY Catalog Number
UPC Number
Description
Status

YA30LB
 7818105048711
 BELLUG-4/0&250FX-1/2 STD
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	2.82
Tongue Type	Standard
Barrell Style	Belled
Bolt Hole Size (in)	0.52
Barrel Type	Standard
Thickness	0.16
B Length (in)	1.04
Pad Width (in)	1.20
Strip Length	1-1/8

General

Number of Holes	1
Product Description	Copper Compression Lug, 1 Hole w/ Inspection Window, 4/0 Flex-250 Flex, 1/2" Stud, Short Barrel, Belled End, Tin Plated

Conductor(s)

Aircraft Cable Size (Range)	N/A
Flex (Class H) Size - Range	250 kcmil
Flex (Class I) Size - Range	4/0 AWG
Copper Solid Size (Range)	N/A
DLO Size (Range)	4/0 (550/#24) DLO
Navy Cable Size (Range)	300 (91) Navy
Copper Stranded (Range)	300 kcmil
Flex (Class G) Size - Range	250 kcmil
Flex (Class M) Size - Range	4/0 AWG

Physical

Type of Plating	Tin - Electro Plated
Bolt Hole Size	1/2
Color Code	White
Plated (Yes or No)	Y
Index Number	17
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175