

Cam-Type Devices



Series 15 - Tees, Gender Reversing Devices and Accessories

Tees, Gender Reversing Devices and Replacement Bodies

Enclosure Types
3R, 4X, 12



	Tapping Tee	Paralleling Tee	Gender Reversing Devices		Replacement Bodies** (25 Pack)	
Color	(Female-Female-Male)	(Female-Male-Male)	Double Male (Male-Male)	Double Female (Female-Female)	Male Body	Female Body
Black	HBL15TBK	HBL15PTBK	HBL15DMBK*	HBL15DFBK*	HBL15MBBK	HBL15FBBK
White	HBL15TW	HBL15PTW	HBL15DMW	HBL15DFW	HBL15MBW	HBL15FBW
Green	HBL15TGN	HBL15PTGN	HBL15DMGN	HBL15DFGN	HBL15MBGN	HBL15FBGN
Red	HBL15TR	HBL15PTR	HBL15DMR*	HBL15DFR*	HBL15MBR	HBL15FBR
Blue	HBL15TBL	HBL15PTBL	HBL15DMBL*	HBL15DFBL*	HBL15MBBL	HBL15FBL

Note: *UL 1691 restricts the use of male-to-male or female-to-female devices to Grounding (Green) or Neutral (White) conductors. Consult factory for availability of other non UL listed colors.

**Additional colors are available upon request. Contact factory.

Protective Caps and Weather Protective Covers

Replacement Contacts (25 Pack)



	Protective Caps	
Color	Fits Male Devices	Fits Female Devices
Black	HBL15MCAPBK	HBL15FCAPBK
White	HBL15MCAPW	HBL15FCAPW
Green	HBL15MCAPGN	HBL15FCAPGN
Red	HBL15MCAPR	HBL15FCAPR
Blue	HBL15MCAPBL	HBL15FCAPBL
**	—	—

Note:**Additional colors are available upon request. Contact factory.

Color	Weather Protective Covers
Clear	HBL15NCC
Black	HBL15NCBK
White	HBL15NCW
Green	HBL15NCGN
Red	HBL15NCR
Blue	HBL15NCBL
Brown	HBL15NCBN
Orange	HBL15NCO
Yellow	HBL15NCY

Description	Male Pin	Female Sleeve
Contact, 150 amp	HBL15RCM	HBL15RCF

Accessories



Accessory Kit	Retaining Screw (100 Pack)	Copper Foil (100 Pack)	Brass Wire (100 Pack)	Terminal Screws (100 Pack)		Ferrules (100 Pack)	
				Inline	Panel Mount	#2 AWG	#4 AWG
HBL15PK	HBL15RS	HBL15CF	HBL15BW	HBL15TS25	HBL15TS375	HBL15F2	HBL15F4

Product Dimensions Inches (mm)

	Tees		Gender Reversing Devices		Weatherproof Covers
	Tapping	Paralleling	Double Male	Double Female	
A	2.67" (67.9)	2.67" (67.9)	4.22" (107.3)	4.22" (107.3)	2.03" (51.5)
B	4.28" (45.9)	4.22" (107.2)	0.86" (21.8)	1.05" (26.7)	1.14" (29.0)
C	0.865" (21.9)	0.865" (21.9)	—	0.68" (17.3)	1.49" (37.9)

