



30 Amp, 125/250 and 3Ø 250 Volts AC 3 Pole, 3 Wire, Non-Grounding and 3 Pole, 4 Wire, Grounding







0A 125/250V A NEMA L10-30P

0A 125/250V A NEMA L14-30P 2 (2) HP

30A 3Ø 250V AC NEMA L15-30P 3 HP



HBL2711SW

Watertight Safety-Shrou	IP66 SUITABILITY UL Type 4x, 12				
Description	Cord Dia.	Catalog Number			
Black Valox® housing, white Valox® clamps.	.350"-1.150" (9-29)	-	HBL2711SW	HBL2721SW	
0-(-1-0110					

Safety-Shroud®			IP20 SUITABILITY	
Description	Cord Dia.	Catalog Number		
Black and white nylon body, white Valox® shroud. Can be used with the Insulgrip Connector Bodies.	.350"-1.150" (9-29)	-	HBL2711S	HBL2721S

Note: See page B-42 for accessories.

4.21" (106.9) 2.23" (56.6) DIA.

HBL2711S

Insulgrip® IP20 SUITABILITY Description Cord Dia. Catalog Number .350"-1.150" HBL2721 HBL2711 Black and white nylon. (9-29)Black and white nylon, .300"-.950" HBL2661 (Not shown). (7.6-24.1)HBL27CM11 HBL27CM21 .350"-1.150" Corrosion resistant, yellow nylon. (9-29)All black nylon. .350"-1.150" **HBL2711BK** (9-29)

Note: See page B-54 for accessories.



HBL2711

Flanged Inlets

Watertight Safety-Shroud®	IP66 SUITABILITY UL Type	e 4x, 12
Description	Catalog Number	
Gray Valox® housing and flange.	- HBL2715SW H	HBL2725SW
Reverse service, gray Valox® housing and flange (use with HBL2713SR), (Not shown).	- HBL2715SWR	-

ľ	Vote:	See	page	B-56	tor	accessories.	

Insulgrip [®]		IP20 SUITABILIT	ſΥ
Description	Catalog Number		
Nylon casing, back wired.	_	HBL2715	HBL2725
Nylon casing, back wired, (Not shown).	HBL2665	-	-
Nylon casing, weather protective, die cast aluminum, back wired, self closing lift cover.	-	HBL2715M3	-

Note: See page B-54 for accessories.

See pages B-71 and B-72 for technical information on Twist-Lock and Watertight Safety-Shroud devices.





Dimensions in Inches (mm)



HBLMITL - For use with Watertight Safety-Shroud receptacles and reverse service inlet, see page B-43.



Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.