


**EMT COMPRESSION COUPLINGS****Compression Couplings, Steel****B06**

Catalog #: 2928US

**APPLICATIONS**

For use in dry locations to couple two ends of EMT conduit  
RACO Compression couplings are suitable for applications above 600V

**PRODUCT FEATURES**

RACO Steel compression couplings provide concrete-tight connections  
All steel construction ensures mechanical protection for the raceway  
All components are zinc electroplated for corrosion protection  
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation.

**CULUS**

Standard 514B, UL Listed E195970, C22.2 No. 18

**COMPLIANCES**

MSDS  
[www.hubbell-rtb.com/certifications/Hubbell-RACO\\_MSDS\\_for\\_WP\\_Boxes\\_and\\_Fittings,January 2015.pdf](http://www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January 2015.pdf)

**GENERAL PRODUCT INFORMATION**

Trade Size: 2 in.

**DRAWING DIMENSIONS**

Dimension A: 2.88 in.  
Dimension B: 2.74 in.

**PACKAGING**

Package Type: Carton  
Ship Carton Qty.: 5  
Product UPC-A Labeled: No  
Weight (Lbs. Per/C): 60.00  
Ship Carton Length (in.): 12.88  
Ship Carton Width (in.): 8.75  
Ship Carton Height (in.): 5.63  
Ctn Weight (Lbs.): 17.50  
UPC Number: 050169570470  
I2of5: 50050169570475