



HSC12T300PF

by Burndy
Catalog ID: HSC12T300PF

Prop65

Heat Shrinkable Cross-Linked Thin Polyolefin Tube, 6 - 2 AWG, 600 V,
Shrink Ratio: 2 : 1,Standard reel size:25 ft.

Features: Type HS-T-PF Is A Flexible Thin Wall, Flame Retardant Heat Shrink Tubing Made Of Crosslinked Polyolefin, The 2:1 Shrink Ratio Allows For Faster Shrink Recovery, Covering Wire Sizes 18 AWG To 300 KCMIL, Operating Temperatures From -55 To 135 DEG C With A Shrink Temperature Of 120 DEG C, Inner Diameter Expanded: 0.5 IN Minimum, Nominal Diameter: 1/2 IN, Material: Cross-Linked Polyolefin, Inner Diameter After Recovery: 0.12 IN Maximum, Conductor Range: 6 - 2 AWG

Product Details

General

Application	For Terminations And Splices
Color	Clear
Material	Polyolefin
Sub Brand	VISISHRINK
Type	HS-T-PF, Thin Wall, Flexible, Flame Retardant
UPC	781810213803

Conductor Related

Conductor Range	#6 AWG to #2 AWG
-----------------	------------------

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)