



Traditional Flush Furniture Feed FRPT 3 Inch Core Hole Units, for Use In Concrete Floors

Large Capacity, Single-Service Flush Furniture Feed FRPT, Two-Piece Units

Description	Catalog Number	Description	Color/Material	Catalog Number
Large Capacity, Single-Service Through Floor Fitting with (1) 2 in. EMT stem. Will accommodate up to 36 Category 6 cables.	PT2FIT	Large Capacity Cover/Flange	Brass Finish Black Gray	FF2BRS FF2BK FF2GY
Specifications: <ul style="list-style-type: none"> 1- to 2-hour fire rating Single-Service, Power or Data For 2¼ to 7 in. floor thickness UL installation spacing – minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area Approved for use in the City of Chicago 		Specifications: <ul style="list-style-type: none"> Cover/flange with 1¼ in. and 2 in. trade size combination knockout Painted aluminum cover and flange Approved for use in the City of Chicago 		



Note: See page Q-44 for technical information.

Flush Furniture Feed FRPT, One-Piece Units


Description	Color	Catalog Number	Description	Color	Catalog Number
3-Service Furniture Feed Poke-Through	Black Gray Ivory	PT73FFSDBK PT73FFSDGY PT73FFSDI	Single-Service Furniture Feed Poke-Through	Black Gray Ivory	PT7FFSDGY PT7FFSDI
Complete assembled unit includes: <ul style="list-style-type: none"> PT73SD floor fitting Aluminum cover with (2) ½ in. threaded hubs for low voltage and (1) ¾ in. threaded hub for power Painted aluminum flange 			Complete assembled unit includes: <ul style="list-style-type: none"> PT71SD floor fitting Aluminum cover with (1) KO to accept a ¾ in. connector Painted aluminum flange 		

Note: See page Q-44 for technical information.

Flush Furniture Feed FRPT, Two-Piece Units

Description	Catalog Number	Description	Catalog Number
3-Service Furniture Feed Through-Floor Fitting with (1) ¾ in. EMT stem for power and (2) ½ in. low voltage conduit holes.	PT73SD	Single-Service Furniture Feed Through-Floor Fitting with (1) ¾ in. EMT stem for power or low voltage applications.	PT71SD
Specifications: <ul style="list-style-type: none"> 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design) 		Specifications: <ul style="list-style-type: none"> For 2¼ to 7 in. floor thickness UL installation spacing – minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area 	

Service Fittings

Description	Color	Catalog Number	Description	Color	Catalog Number
3-Service Furniture Feed Service Fitting	Black Gray Ivory	FRF3BK FRF3GY FRF3I	Single-Service Furniture Feed Service Fitting	Brass Finish Black Gray	FRF1BRS FRF1BK FRF1GY
Complete assembled unit includes: <ul style="list-style-type: none"> Aluminum cover with (2) ½ in. threaded hubs for low voltage and (1) ¾ in. threaded hub for power Painted aluminum flange 			Complete assembled unit includes: <ul style="list-style-type: none"> Aluminum cover with (1) KO to accept a ¾ in. connector Painted aluminum flange 		

Note: See page Q-35 for 3 Inch FRPT accessories.
See page Q-44 for technical information.