

Low Profile Power Packs

FEATURES

- Low Profile power pack for use with linear or long compact fluorescent lamps
- Compatible with electronic, magnetic, energy saving or dimming AC ballasts
- Sealed nickel-cadmium battery; no AC ballast required for emergency only luminaires
- Can be used with switched or unswitched luminaires
- Installation may be mounted inside or on top of the luminaire
- Compatible with AC ballasts having End-of-Lamp-Life feature
- 120/277VAC 60Hz operation, test switch and AC-On indicator light
- Temperature range: 0°C to 50°C (32°F to 122°F)
- UL 924 Damp Location Listed



BATTERY PACKS

ORDERING INFORMATION



MODEL

UFO-LP1
UFO-LP2

SPECIFICATIONS

CATALOG NUMBER	INPUT WATTAGE	LAMP TYPE	LAMP EXAMPLES	1 LAMP LUMENS
UFO-LP1	2.6	T5	FP54, F54T5/HO	700
			FP39, F39T5/HO	620
			FP24, F24T5/HO	390
			FP28, F28T5	700
			FP21, F21T5	620
			FP14, F14T5	430
		T8	F32T8, (4')	635
			F40T8 (5')	570
			F40T8/HO (4', 44W)	470
		Long CFL 4-pin	PL-L 50W, F50BX/RS, Dulux L 55W	510
			PL-L 40W, F40/30BX, Dulux L 40W	625
			PL-L 36W, F39/36BX, Dulux L 36W	610
UFO-LP2	3.0	T5	FP54, F54T5/HO	1250
			FP39, F39T5/HO	1125
			FP24, F24T5/HO	725
			FP28, F28T5	1250
			FP21, F21T5	1025
			FP14, F14T5	750
		T8	FP17T8	650
			FP25T8	750
			F32T8, (4')	1100
			F40T8 (5')	1325
			F40T8/HO (4', 44W)	1275
		Long CFL 4-pin	PL-L 50W, F50BX/RS, FT55DL	1050
			PL-L 40W, F40/30BX, FT40DL/RS	925
			PL-L 36W, F39/36BX, FT36DL	900

ACCESSORIES

MODEL	DESCRIPTION
F-WC	Wire bundle cover ¹
SPRTS	Remote test switch/charge indicator module ²

¹Encloses exposed wiring harness when power pack is externally mounted on the lighting fixture. One required per fixture.

²Fits single-gang box.

