

YCS321RL

by Burndy
Catalog ID: YCS321RL

Prop65

HYSPLICE AL sleeve with staked cable stop, designed to withstand jumper loop tensile and vibration stresses. ANSI C119.4 CLASS 2 (PARTIAL TENSION), Index:655.

Features: Aluminum Jumper Sleeve, With Cable Stop, Designed To Be Installed With Same Dies As Equivalent Full-Tension UNISPLICE, Withstands Jumper Loop-Tensile And Vibration Stresses, Pre-Filled With PENETROX Joint Compound And Capped, Accommodates ACSR With Aluminized Steel Core, Tools, Die Set Catalog Number, And (number Of Crimps): Y35, Y750 Tool, U655 Die, (3), Y45 Tool, U655 Die With PT-6515 Adapter, (3), Y46 Tool, U655 Die With PUADP-1 Adapter, (3), Die Index: 655 Element A, Conductor Type: ACSR, 6201, 5005, Commercial Aluminum

Product Details

General

Application	For ACSR, All Aluminum 6201, 5005 Compressed And Compact Conductors
Connector Type	Splice
Die Index	655
Item Type	3B
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	UNISPLICE
Trade Name	UNISPLICE™
Type	YCS-RL
UPC	781810015124
UPC 12 Digit	7818100151244

Dimensions

Dimension - B Length inch	2.25 in
Dimension - L Length Overall mm	131 mm
Dimension - Length Overall inch	5.16 in
Dimension - Outside Diameter inch	1.13 in

Conductor Related

Conductor - ACSR Str Size	336.4 (18/1) Merlin
Conductor - AL Str Size	336.4

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No

Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	25
-----------------------	----

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)