


**30 Amp, 125, 250 Volts and 277 Volts AC  
2 Pole, 3 Wire, Grounding**




**HBL2611SW**



**HBL2621S**




**HBL2621**



**HBL2611VY**



**HBL2615SW**



**HBL2625**

## Plugs

### Watertight Safety-Shroud®

| Description                                | Cord Dia.          | Catalog Number   | IP66 SUITABILITY | UL Type 4x, 12 |
|--------------------------------------------|--------------------|------------------|------------------|----------------|
| Black Valox® housing, white Valox® clamps. | .325"-.930" (9-24) | <b>HBL2611SW</b> | <b>HBL2621SW</b> | —              |

### Safety-Shroud®

| Description                                                                                       | Cord Dia.          | Catalog Number  | IP20 SUITABILITY  |
|---------------------------------------------------------------------------------------------------|--------------------|-----------------|-------------------|
| Black and white nylon body, white Valox® shroud. Can be used with the Insulgrip Connector Bodies. | .360"-.930" (9-24) | <b>HBL2611S</b> | <b>HBL2621S</b> — |

Note: See page B-42 for accessories.

### Insulgrip®

| Description                                          | Cord Dia.          | Catalog Number   | IP20 SUITABILITY              |
|------------------------------------------------------|--------------------|------------------|-------------------------------|
| Black and white nylon.                               | .360"-.930" (9-24) | <b>HBL2611</b>   | <b>HBL2621</b> <b>HBL2631</b> |
| Heat stabilized, gray nylon, 220° F (104° C).        | .360"-.930" (9-24) | <b>HBL2611F</b>  | <b>HBL2621F</b> —             |
| Corrosion resistant, yellow nylon.                   | .360"-.930" (9-24) | <b>HBL26CM11</b> | <b>HBL26CM21</b> —            |
| All black nylon.                                     | .360"-.930" (9-24) | <b>HBL2611BK</b> | <b>HBL2621BK</b> —            |
| Cord clamps with removable inserts. All black nylon. | .360"-.930" (9-24) | —                | <b>HBL2621EBK</b> —           |

Note: See page B-54 for accessories.

### Valise®

| Description                        | Cord Dia.               | Catalog Number    | IP20 SUITABILITY    |
|------------------------------------|-------------------------|-------------------|---------------------|
| Yellow nylon.                      | .590"-.930" (15.0-23.6) | <b>HBL2611VY</b>  | <b>HBL2621VY</b> —  |
| Corrosion resistant, yellow nylon. | .590"-.930" (15.0-23.6) | <b>HBL26CM11V</b> | — —                 |
| Black nylon.                       | .590"-.930" (15.0-23.6) | <b>HBL2611VBK</b> | <b>HBL2621VBK</b> — |

Note: See page B-55 for accessories.

## Flanged Inlets

### Watertight Safety-Shroud®

| Description                                                                        | Catalog Number    | IP66 SUITABILITY | UL Type 4x, 12 |
|------------------------------------------------------------------------------------|-------------------|------------------|----------------|
| Gray Valox® housing and flange.                                                    | <b>HBL2615SW</b>  | <b>HBL2625SW</b> | —              |
| Reverse service, gray Valox® housing and flange (use with HBL2613SR), (Not shown). | <b>HBL2615SWR</b> | —                | —              |

Note: See page B-56 for accessories.

### Insulgrip®

| Description                                                                               | Catalog Number   | IP20 SUITABILITY              |
|-------------------------------------------------------------------------------------------|------------------|-------------------------------|
| Nylon casing, back wired.                                                                 | <b>HBL2615</b>   | <b>HBL2625</b> <b>HBL2635</b> |
| Heat stabilized, gray nylon, 220° F (104° C).                                             | <b>HBL2615F</b>  | <b>HBL2625F</b> —             |
| Nylon casing, weather protective, die cast aluminum, back wired, self closing lift cover. | <b>HBL2615M3</b> | — —                           |

Note: See page B-54 for accessories.

See pages B-71 and B-72 for technical information on Twist-Lock and Watertight Safety-Shroud devices.  
See page B-76 for technical information on Valise plugs and connectors.

Dimensions in Inches (mm)

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.