




## SINGLE DEVICE HANDY BOXES & EXTENSION RINGS

4 in. x 2 in. Handy Boxes, 1-7/8 in. Deep - Drawn with Conduit KO's  
Raised Ground, TS Bracket, 1/2 in. Setback

A44



Catalog #: 662

### APPLICATIONS

RACO® Handy boxes, also called utility boxes, are used for convenience outlets, switch boxes or small junction boxes. They are popular for exposed work applications (surface mounted wiring). The NEC requires that surface-mounted wiring be enclosed with a protective covering such as EMT conduit.

### PRODUCT FEATURES

Reference the Box Selection section in the front of this catalog for complete description of bracket types and features  
N/A

### UL LISTED

File E195978

### COMPLIANCES

All RACO® single gang, two gang, 4 in. square, and single gang gangable UL listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult UL "Fire Resistance Directory" or the UL website at [www.ul.com](http://www.ul.com)

### FIRE RESISTANCE

Acceptable for use in 2-hour rated walls

### GENERAL PRODUCT INFORMATION

Wiring System: Conduit

### CONFIGURATION

End Knockouts: (2) 1/2 in.  
Bracket Type: TS, for Metal or Wood Studs  
Bracket Setback: 1/2 in.  
Drawn or Welded: Drawn  
Raised Ground: Yes  
Side Knockout(s): (3) 1/2 in.  
Bottom Knockouts(s): (3) 1/2 in.

### DRAWING DIMENSIONS

Dimension A: 1-7/8 in.  
Dimension B: 7 in.  
Dimension C: 2-3/8 in.

### PRODUCT MEASUREMENTS

Depth: 1-7/8 in.  
Cubic Inches (cm<sup>3</sup>): 13.0 (213.0)  
Wt. Ea. (Lbs.): 0.601  
Product Length (in.): 1.94  
Product Width (in.): 7.00  
Product Height (in.): 2.38

### PACKAGING

Minimum Pack Qty.: 25  
Std. Pkg.: 25  
Product UPC-A Labeled: Yes  
Weight (Lbs. Per/C): 60.10  
Ship Carton Length (in.): 16.75  
Ship Carton Width (in.): 6.00  
Ship Carton Height (in.): 9.63  
Ctn Weight (Lbs.): 15.03  
Pallet Qty: 1500  
UPC Number: 050169006627  
I2of5: 40050169006625