## Single Pole Devices and Temporary Power



### Series 15 - 150 Ampere, 600V AC/250V DC

**Enclosure Types** 3R, 4X, 12



Gender Reversing Devices	1	( ) Year
Color	Double Male (Male-Male)	Double Female (Female-Female)
Black White Green Red Blue	HBL15DMBK* HBL15DMW HBL15DMGN HBL15DMR* HBL15DMBL*	HBL15DFBK* HBL15DFW HBL15DFGN HBL15DFR* HBL15DFBL*

Note: \*UL 1691 restricts the use of male-to-male or female-to-female devices to Grounding (Green) or Neutral (White) conductors. Consult factory for availability of other non UL listed colors.

# Replacement **Bodies** (25 Pack)

Color	Male Body	Female Body
Black	HBL15MBBK	HBL15FBBK
White	HBL15MBW	HBL15FBW
Green	HBL15MBGN	HBL15FBGN
Red	HBL15MBR	HBL15FBR
Blue	HBL15MBBL	HBL15FBBL
**	_	_

Note: \*\*Additional colors are available upon request. Contact factory.

### Replacement **Contacts** (25 Pack) Description Male Pin Female Sleeve Contact, HBL15RCM HBL15RCF 150 amp

#### **Accessories**

Description	Catalog Number
Accessory Kit, retaining screw, copper foil, terminal screws and brass wire.	HBL15PK
Replacement retaining screw (100 pack).	HBL15RS
Copper foil (100 pack).	HBL15CF
Brass wire (100 pack).	HBL15BW
Terminal screw - inline (100 pack).	HBL15TS25
Terminal screw - panel mount (100 pack).	HBL15TS375
Ferrule #2 AWG (100 pack).	HBL15F2
Ferrule #4 AWG (100 pack).	HBL15F4



