

YTA2R2N

by Burndy
Catalog ID: YTA2R2N

Prop 65 Notice

AL primary T-tap connector with slotted tap pad designed for easy disconnecting of tap conductor, For use with Types YKA-R-2N and YKA-A-2N, Barrel Length: .88 IN



Product Details

General

Connector Type	Tap
Die Index	243;BG
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	N
Type	YTA Series
UPC	781810013946
UPC 12 Digit	7818100139466

Dimensions

Dimension - B Length inch	0.88 in
Dimension - Bolt Size fraction	1/2
Dimension - Height inch	4.34 in
Dimension - L Length Overall mm	155 mm
Dimension - Length Overall inch	6.09 in

Conductor Related

Conductor - ACSR Str Size	2 (6/1) Sparrow AWG;2 (7/1) Sparate AWG
Conductor - ACSR Str Size Range	2 (6/1) Sparrow AWG-2 (7/1) Sparate AWG
Conductor - AL Str Size	2 AWG;1 AWG
Conductor - AL Str Size Range	2 AWG-1 AWG
Conductor - Copper Str Size	2 AWG;1 AWG
Conductor - Copper Str Size Range	2 AWG-1 AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No

Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	7
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)