


**EMT COMPRESSION COUPLINGS****Compression Couplings, Steel****B06**

Catalog #: 2924US

APPLICATIONS

For use in dry locations to couple two ends of EMT conduit
RACO Compression couplings are suitable for applications above 600V

PRODUCT FEATURES

RACO Steel compression couplings provide concrete-tight connections
All steel construction ensures mechanical protection for the raceway
All components are zinc electroplated for corrosion protection
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation.

CULUS

Standard 514B, UL Listed E195970, C22.2 No. 18

COMPLIANCES

MSDS
www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January_2015.pdf

GENERAL PRODUCT INFORMATION

Trade Size: 1 in.

DRAWING DIMENSIONS

Dimension A: 2.32 in.
Dimension B: 1.64 in.

PACKAGING

Package Type: Carton
Std. Pkg.: 20
Ship Carton Qty.: 100
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 19.00
Ship Carton Length (in.): 11.38
Ship Carton Width (in.): 9.00
Ship Carton Height (in.): 11.25
Ctn Weight (Lbs.): 33.20
UPC Number: 050169570449
I2of5: 50050169570444