

YSP28T

by Burndy
Catalog ID: YSP28T

Prop65

Uninsulated high voltage Cu -code compression splice, Tapered end, 4/0 STR, 600V-35KV, Tin plated, 15 Index.

Features: Seamless Types YSP-T High Conductivity Copper Electro-Tin Plated Compression HYLINK High-Voltage Splices With Long Barrel And Tapered Ends Are Ideally Suited For Higher Voltage Applications From 5KV Through 35 KV, Tapered Connector Ends Per EEI Standard TD160, Suitable For Use On Voltages 5KV Through 35KV To Aid In Preventing Corona Emission And Simplify Taping Thus Lowering Installed Cost, Type YSP-T Has A Center Plug Permanently Brazed In Place: Prevents Oil Within Oil-Filled Conductors From Passing Through The Splice Connector And Provides A Center Strip For Proper Conductor Insertion, Installation Tool: Y34B, Y34PR Indentor, B28D Nest Die, Oil Stop: Yes, Tapered End: Yes, Tools, Die Nest Catalog Number, Die Indentor Catalog Number: Y35, Y39, Y750 Tool, U28D-1 Nest Die, Y34PR Indentor, Y35P3 Adapter, Die Index: 15 Element A, Wire Strip Length: 1-3/16 IN, Tools, Die Set Catalog Number, And (number Of Crimps): PAT750 Tool, U28RT Die, (2), Y35, Y39, Y46, Y750 Tool, U28RT Die With PUADP-1 Adapter, Conductor Type: Commercial Stranded Copper

Product Details

General

| | |
|------------------------|---------------------------------------------------------|
| Application | For Higher Voltage Applications From 5 KV Through 35 KV |
| Color Code | Purple |
| Connector Type | Splice |
| Feature - Barrel Style | Tapered |
| Feature - Barrel Type | Standard |
| Material | Copper |
| Plated | Y |
| Plating Type | Electro Tin plated |
| Sub Brand | HYLINK |
| Trade Name | HYLINK™ |
| Type | YSP-T, High Voltage, Long Barrel |
| UPC | 781810001301 |

Dimensions

| | |
|---------------------------------|-----------|
| Dimension - B Length inch | 1.16 in |
| Dimension - L Length Overall mm | 62 mm |
| Dimension - Length Overall inch | 2.45 in |
| Dimension - Strip Length inch | 1-3/16 in |

Conductor Related

| | |
|-----------------------------|---------|
| Conductor - Copper Str Size | 4/0 AWG |
|-----------------------------|---------|

Certifications and Compliance

| | |
|------------------------------|----|
| Certification - CSA Approved | No |
|------------------------------|----|

| | |
|------------------------------------|-----|
| Certification - ETL | No |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

Logistics

| | |
|-----------------------|---|
| Minimum Pack Quantity | 1 |
|-----------------------|---|

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)