

Ordering Information

Description	UPC Number	Catalog Number
3P 4W LINKOSITY® male receptacle for installation on motor	783585116280	RM3004PA001




Listings

UL 2238; UL 50E

Performance

Electrical	
Amperage	Up to 30A
Voltage	Up to 600V AC
Environmental	
Flammability	UL94V-0
Ingress Protection	IP67 Suitability
Moisture Resistance	UL Type 4, 4X, 12 and 13



Complementary Products

Type 1 Non-Metallic Enclosure 30A 3 Pole 600V AC	HBL1389MQR, HBL1389MQ5, HBL1389MQR2
Type 4X Non-Metallic Labelless Enclosure 30A 3 Pole 600V AC	HBLDS3MQR, HBLDS3MQ5, HBLDS3MQR2
Type 4X Stainless Steel Enclosure 30A 3 Pole 600V AC, Sloped	HBLDS3SSRMQR, HBLDS3SSRMQ5, HBLDS3SSRMQR2
Type 4X Stainless Steel Enclosure 30A 3 Pole 600V AC, Square	HBLDS3SSMQR, HBLDS3SSMQ5, HBLDS3SSMQR2

Online Resources

Customer Use Drawing
eCatalog
Installation Instructions

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.