


**EMT COMPRESSION CONNECTORS**

Compression Connectors, Steel

**B05**

Catalog #: 2916US

**APPLICATIONS**

For use to bond EMT conduit to a box or enclosure.  
RACO Compression connectors are suitable for applications above 600V.

**PRODUCT FEATURES**

1/2 in. to 4 in. connectors provide concrete-tight connections  
All steel construction ensures mechanical protection for the raceway  
All components are zinc electroplated for corrosion protection  
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation.

**CULUS**

Standard 514B, UL Listed E195970, C22.2 No. 1

**COMPLIANCES**

MSDS  
[www.hubbell-rtb.com/certifications/Hubbell-RACO\\_MSDS\\_for\\_WP\\_Boxes\\_and\\_Fittings,January\\_2015.pdf](http://www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January_2015.pdf)

**GENERAL PRODUCT INFORMATION**

Sub Class: Insulated  
Trade Size: 1-1/2 in.

**DRAWING DIMENSIONS**

Dimension A: 2.25 in.  
Dimension B: .70 in.  
Dimension C: 2.27 in.

**PACKAGING**

Package Type: Carton  
Std. Pkg.: 5  
Ship Carton Qty.: 25  
Product UPC-A Labeled: No  
Weight (Lbs. Per/C): 46.00  
Ship Carton Length (in.): 11.50  
Ship Carton Width (in.): 6.63  
Ship Carton Height (in.): 5.06  
Ctn Weight (Lbs.): 11.96  
UPC Number: 050169570401  
I2of5: 50050169570406