#### Accessories for 20 and 30 Amp 3, 4 and 5 Wire Devices

## Insulgrip<sup>®</sup> Plug and Connector Body Latching Kit

The Hubbell latching kit provides both improved safety and security through a double locking feature that makes unintentional disconnection virtually impossible - even under high vibration situations. The plug and connector body lock once when first connected, then again when you push the special position locking slide into place.

# Insulgrip<sup>®</sup> Latching Kit

6

Description	For 3 Wire Devices	For 4 & 5 Wire Devices
For all 20A and 30A Twist-Lock Insulgrip plugs and connectors.	SK2	SK3

IP55\*

IP55\*

\_

Valise®	SUITABILITY	
Weatherproof, Seal-Tite <sup>®</sup> , Triple Seal Boots		
Description	For 3 Wire Devices	For 4 & 5 Wire Devices
Yellow Seal-Tite <sup>®</sup> elastomer triple seal cover for use with Valise plugs when used in cord set and Valise connector	HBL60CM31V	-

bodies when used with flanged inlet. Yellow Seal-Tite<sup>®</sup> elastomer triple seal cover for use with HBL60CM32V Valise connector bodies.

Note: \*When installed and used properly with plug and connector body combinations.

Insulgrip <sup>®</sup>	SUITAB
Weatherproof, Seal-Tite <sup>®</sup> , Triple Seal Boots	

Description	For 3 Wire Devices	For 4 & 5 Wire Devices
Black elastomer boot for plugs when used in a cord set and connector bodies when used in flanged inlets.	HBL6031	HBL6035
Same as above except yellow.	HBL60CM31	HBL60CM35
Black elastomer boot for connector bodies when used in a cord set.	HBL6032	HBL6036
Same as above except yellow.	HBL60CM32	HBL60CM36

### Angle Adapter

Е

Description	For 3 Wire Devices	For 4 & 5 Wire Devices	
Nylon, angle adapter for Insulgrip plugs and connector bodies, cord grip range .325"930" (8.3-24).	HBL3WAA	HBL45WAA	
PLUGOUT <sup>®</sup> Lockout Devices			
Description	For 3 Wire Devices	For 4 & 5 Wire Devices	
Lockout device for attachable 20 and 30A locking plugs, straight body or angle types, with or without weatherproof covers.	HLD	HLD	
Lockout device for 20 and 30A 3 wire angle plugs and watertight Safety-Shroud <sup>®</sup> Twist-Lock <sup>®</sup> plugs.	HLD2	HLD2	

Note: See section BB for additional information on PLUGOUT Lockout devices. \*When installed and used properly with plug and connector body combinations.

For quick visual identification of circuits or configurations.

### **Colored Cord Clamps\***

Description	Color	For 3 Wire Devices	For 4 & 5 Wire Devices
For use with 20A and 30A Insulgrip <sup>®</sup> Twist-Lock <sup>®</sup>	Black	HBLTL2CCBK	HBLTL3CCBK
Plugs and Connectors. Cord diameter: 3 wire	Blue	HBLTL2CCBL	HBLTL3CCBL
.350"930" (9-24), 4 & 5 wire .350" – 1.150" (9-29)	Brown	HBLTL2CCBR	HBLTL3CCBR
	Dark Blue	HBLTL2CCDB	HBLTL3CCDB
	Green	HBLTL2CCGR	HBLTL3CCGR
	Orange	HBLTL2CCOR	HBLTL3CCOR
	Red	HBLTL2CCRD	HBLTL3CCRD
	Teal	HBLTL2CCTL	HBLTL3CCTL
	White	HBLTL2CCWH	HBLTL3CCWH
	Yellow	HBLTL2CCYL	HBLTL3CCYL

Note: \*Clamp only. Contains no screws. Order in increments of 10. Not UL Listed or CSA Certified.







HBL60CM31V



HBL6032





HLD



Dimensions in Inches (mm)

HUBBELL<sup>®</sup> Wiring Device-Kellems