

M-10316 3

 $1.322 \pm .015$
 $[33.58 \pm .40]$
 $3.281 \pm .015$
 $[83.34 \pm .40]$

#6-32 TAP

 $1.569 \pm .015$
 $[39.86 \pm .40]$
 $1.067 \pm .015$
 $[27.10 \pm .40]$
 $.830 \pm .015$
 $[21.08 \pm .40]$
 $2.731 \pm .015$
 $[69.37 \pm .40]$

NOTES:

- 1) DIMENSIONS ARE IN INCHES (MM).
- 2) ALL DEVICES UL LISTED, CSA AND FED. SPEC. CERTIFIED.
- 3) TERMINALS ACCOMMODATE #14-#10 AWG COPPER WIRE ONLY.

CATALOG NUMBERS

	BROWN	IVORY	GRAY	WHITE	BLACK	ALMOND	BLUE	LIGHT ALMOND	RED	ORANGE	OFFICE WHITE
HUBBELL	CR15	CR15I	CR15GRY	CR15WHI	CR15BLK	CR15AL	CR15BL	CR15LA	CR15R	-----	CR15OW

CODE 74545

LIST OF PARTS

DESCRIPTION	MATERIAL	FINISH
TOP	NYLON 6/6	SPI A-3
BASE	NYLON 6/6	SPI A-3
LINE CONTACTS	BRASS	
GROUND CONTACTS	BRASS	
CONTACT SCREW (NEU)	STEEL	NI PLT
CONTACT SCREW (HOT)	STEEL	
BRIDGE	.04 GALV STL	
GROUND SCREW	STEEL	GREEN
STAPLE	S.S.	
WASHER	PVC FILM	BLACK
MOUNTING SCREW	STEEL	ZINC PLT

3	ADDED CAT. NOS. CR15BL & CR15R TO TABLE. PER DCP	DJP	11/16/12
2	ADDED CAT. NOS. CR15AL & CR15LA PER DCP# 13864	WRV	08/02/07
1	RELEASED PER DCP# 13786	WRV	03/27/07

SYM REVISIONS APP DATE

THE DESIGN AND DIMENSIONS OF THE
PRODUCT SHOWN ON THIS DRAWING ARE
SUBJECT TO CHANGE WITHOUT NOTICE

TITLE HUBBELL
15A 125V, 2P 3W,
SMOOTH FACE DUPLEX RECEPT.
SIDE WIRE

TOLERANCES UNLESS
OTHERWISE SPECIFIED

.XX : $\pm .01$
 .XXX : $\pm .005$
 ANGLES : $\pm 2^\circ$

WIRING DEVICE KELLEMS
HUBBELL INCORPORATED
SHELTON, CT

DR. BY WRV	APP. BY
TR. BY	SCALE 1:1
CHK. BY	DATE 3/07

DIMENSION SHEET FOR CAT. NO.

REPAIRABLE ☐ NON-REPAIRABLE ☐

B

M-10316

3