



BURNDY Catalog Number
UPC Number

YAV4CL2NT14FX
7818102950211
CUHYLUG #4 2HOLE 1/4 STUD FX
NT
Active

Description
Status

Web Use
BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	2.08
Barrell Style	Chamfered
Bolt Hole Size (in)	0.27
Barrel Type	Standard
Thickness	0.09
B Length (in)	0.50
Pad Width (in)	0.45
E - in	0.63
Strip Length	9/16

General

Number of Holes	2
Product Description	Copper Compression Lug, Narrow Tongue, 2 Hole w/ Inspection Window, 4 Flex, 1/4" Stud, 5/8" Stud Hole Spacing, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range	4 AWG
Flex (Class H) Size - Range	4 AWG
Flex (Class I) Size - Range	4 AWG
Copper Solid Size (Range)	4 AWG
DLO Size (Range)	5 (91/#24) DLO-4 (105/#24) DLO
Copper Stranded (Range)	4 AWG

Physical

Type of Plating	Tin - Electro Plated
Bolt Hole Size	1/4
Color Code	Gray
Plated (Yes or No)	Y
Index Number	8
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175