EMT SET SCREW CONNECTORS

Uninsulated Set Screw Connector, Steel







Catalog #: 2140US

APPLICATIONS

For use in dry locations to bond EMT conduit to a box or enclosure. RACO steel set screw connectors provide concrete-tight connections when taped. For use in dry locations to bond unthreaded rigid/IMC conduit to a box or enclosure. RACO steel set screw connectors provide concrete-tight connections when taped.

PRODUCT FEATURES

All steel construction ensures mechanical protection for the raceway

Tri-head screws may be installed using a slotted, Phillips, or Robertson head screwdriver 2-1/2 in. to 4 in. trade sizes are also UL listed for use on EMT or Rigid/IMC conduit, allowing for design and installation flexibility

All components are zinc electroplated for corrosion protection

1/2 in. to 1 in. trade sizes have one set screw, 1-1/4 in. to 4 in. trade sizes have two set screws

UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation

ULLISTED

2-1/2" - 4" Standard 514B, File E195969, E195970 Standard 514B, UL Listed E195969

CULUS

1/2" - 2" Standard 514B, C22.2 # 18

COMPLIANCES

MSDS

www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January 2015.pdf

GENERAL PRODUCT INFORMATION

Uninsulated Sub Class: Trade Size 2-1/2 in. Country of Origin: USA

DRAWING DIMENSIONS

3.20 in. Dimension A: Dimension B: 2.93 in. .654 in. 1/4 - 28 Dimension D: Dimension E:

PACKAGING

Package Type: Carton Ship Carton Qty.: Product UPC-A Labeled: Weight (Lbs. Per/C): Νo 142.00 Ship Carton Length (in.): Ship Carton Width (in.): 9.38 7.25 Ship Carton Height (in.): 3.50 Pallet Qty: UPC Number: 750

050169570180