



YA32L2NT38FX

by Burndy
Catalog ID: YA32L2NT38FX

Prop 65 Notice

Cu compression narrow toungue std barrel-Flex conductor, 2 holes/W/
insp window, 313.1 kcmil.775/24 300 flex,600V-35Kv, 3/8" stud, Red, 18
index

Product Details

General

Color Code	Red
Connector Type	Terminal
Die Index	18
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Material	Copper
Physical Attribute - Number of Holes	2
Plated	Y
Plating Type	Tin - Electro Plated
Trade Name	HYLUG™
UPC	781810174371

Dimensions

Dimension - B Length fraction	1-3/16 in
Dimension - B Length inch	1.19 in
Dimension - Bolt Hole Size inch	0.39 in
Dimension - Bolt Size fraction	3/8
Dimension - D inch	1.84 in
Dimension - L Length Overall mm	94 mm
Dimension - Length Overall inch	3.69 in
Dimension - N inch	0.41 in
Dimension - Outside Diameter inch	0.95 in
Dimension - Pad Width inch	0.96 in
Dimension - Strip Length inch	1-1/4
Dimension - Stud Size inch	3/8
Dimension - Z inch	0.43 in
Physical Attribute - Tongue Angle	Straight

Electrical Ratings

Rating - KVA	35 kV
Rating - Minimum Voltage	600

Voltage - Maximum	35000
-------------------	-------

Conductor Related

Conductor - Copper DLO Size	313.1 (775/#24)
Conductor - Copper DLO Size Range	313.1 (775/#24)
Conductor - Copper Flex G Size	313
Conductor - Copper Flex G Size Range	313
Conductor - Copper Flex H Size	313
Conductor - Copper Flex H Size Range	313
Conductor - Copper Flex I Size	313
Conductor - Copper Flex I Size Range	313
Conductor - Copper Flex K Size	313
Conductor - Copper Flex K Size Range	313
Conductor - Copper Flex M Size	313

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	50
-----------------------	----

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)