



## YHSS10

by Burndy  
Catalog ID: YHSS10

Cu Heat Shrink Butt Splice, 10-12 AWG, 1.60" L, Serrated bbl, Tin plated,  
For Use On Cu Cond.

Features: Made From Pure Copper, Annealed For Maximum Strength,  
Color-Coded, Imprinted With Wire Size, Serrated Barrels Offer Maximum  
Wire Contact And Tensile Strength, Electro Tin Plated For Corrosion  
Resistance, Wire Strip Length 5/16 IN, Recommended Tooling MR22,  
Conductor Type: Copper, Wire Strip Length: 5/16 IN

## Product Details

### General

Application	For Use On Copper Conductor
Connector Type	Splice
Insulation	Y
Insulation Type	Heat Shrink
Material	Copper
Plated	Y
Plating Type	Tin
Sub Brand	HYDENT
Trade Name	HYDENT™
Type	YHS, Heat Shrink
UPC	781810476918

### Dimensions

Dimension - B Length fraction	1/4 in
Dimension - B Length inch	0.25 in
Dimension - L Length Overall mm	41 mm
Dimension - Length Overall inch	1.60 in
Dimension - Strip Length inch	5/16

### Conductor Related

Conductor - Copper Solid Size	12 AWG;11 AWG;10 AWG
Conductor - Copper Solid Size Range	12 AWG-10 AWG
Conductor - Copper Str Size	12 AWG;10 AWG
Conductor - Copper Str Size Range	12 AWG-10 AWG
Conductor Type	<ul style="list-style-type: none"> <li>• CU C Solid-Size</li> <li>• CU C Str-Size</li> </ul>

### Certifications and Compliance

Standards - RoHS Compliance Status	CM
------------------------------------	----

### Logistics

Carton Quantity	100 EA
-----------------	--------

Minimum Pack Quantity	100
Packaging Type	Bag

**For further technical assistance, please contact us**

**BURNDY Headquarters**

47 East Industrial Park Drive  
Manchester, New Hampshire 03109

**Customer Service Hours:**

8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)