Wire Basket Tray System

Accessories for Wire Basket Tray, Supports and Fittings

Description	Tray Width	Finish	Catalog Numbe	r	Description	Finish	Catalog Number
	4" (102)	Black	HBTRD4BK		Fitting Attachment	Pre-Galvanized	HBTFA2
	4 (102) 6" (152)	Black	HBTRD6BK	See.	Fills the gap in tray when	Black	HBTFA2BK
	12" (305)	Black	HBTRD12BK		creating fittings in 2" tray	DIAUN	
able bend control;	(300)	DIACK			or 4"/6" tray	Pre-Galvanized	HBTFA46
l per box				P.	·· -· ,	Pre-Gaivanized Black	HBTFA46BK
	4X4	Black	HBTEXTRDE		Deals Attack second	-	-
	474 Minimum	DIGUN			Rack Attachment	Zinc Plated	HBTRA
	Tray Size			AST	Attaches tray directly to	Black	HBTRABK
	Tray Size				the top of a standard rack		
protection and				1.	-		
cable bend control;				~	Conduit Attachment	Pre-Galvanized	
l per box					Connects conduit to tray	Black	НВТСАЗВК
	7¾" (102)	Zinc Plated	HBTVD	133	(¾", 1" and 1¼" conduit)		
Protects cables		Black	HBTVDBK				
when dropping					Nut and Bolt Sets	Zinc Plated	HBTNB
rom the end or				~	1/4" - 20 nut and bolt sets;	Stainless Steel	HBTNBSS
side of tray;					50 pieces per box		
l per box							
_abel Clip		White	HBTLC		Cable Drop Outs	Black	НВТСОВК
Attachment for all size	es of tray;				Black polymer inserts;	DIACK	
l per box					Installed into the bottom of		
 Cable Guide*		Black	HBTCG	-1	the basket tray to reduce		
	-1	DIACK	пыса		pinch points and maintain		
Maintains cable bend				ALT	a radius bend on the		-1
and acts as a divider				AND IN THE REAL PROPERTY OF	exiting cables		
straight sections and	a iitungs;				Large Cable Drop Outs	Black	HBTCD4X4BK
l per box					Black polymer inserts;	DIAUN	
Electrical Box Brac		Pre-Galvanized	HBTEB		Installed into the bottom		
Attaches electrical bo	ox to	Black	HBTEBBL	UNHER	of the basket tray to		
ide of tray; 1 per bo	XC			Here	reduce pinch points and		
				and the second second	maintain a radius bend		
Sidecar		Pre-Galvanized	HBTSC	A.	on the exiting cables (tray		-
ttaches to outside o	of trav	Black	HBTSCBK	f p	requires cutting to install)		
provides additional c		DIAUN			Strut Clips	Pre-Galvanized	HBTSTRUTCLIP
upport, 2" deep; 1 j					Used to hold down		
					basket tray when used		A all >
Splice Kit		Zinc Plated	HBTSK	NB0 🚱	with any standard		3.7.9
piece staked bolt/wa		Black	HBTSKBK	ALL MAN	industry strut supports;		
ut combination; splice		Stainless Steel	HBTSKSS		50 pieces per box	• 12" trays or sr	maller use 2 clips per strut support
ections and field form	iea ittings;			05		• 16" - 18" trays	s use 3 clips per strut support
0 pieces per box						Larger trays a	dd one clip per strut support for
Bar Splice		Zinc Plated HBTBS				every 6" of tra	
lotted bar 11 ¹⁵ /16" lo		Black	HBTBSBK	100	Grounding Split Bolts	Copper Alloy	HBTSPLITBOLTPK10
plices straight secti		Stainless Steel	HBTBSSS		These are sold in packs		
tings; bend to form					of 10. Bolts are used for		
educers; adds rigidit			-		supplemental grounding.		
olices; 50 pieces pe	er box		~		One bolt is installed per		
orner Splice		Zinc Plated	HBTCS		section of basket tray.		
2) 90° splice bars and	d	Black	HBTCSBK		The installer must supply		
) sets of the splice k			HBTCSSS	1	#6 AWG grounding wire		.
		Stainless Steel		Casto P. 10	#0 Avva grounding wire		
plice Fittings Req				W 18 18			
se one per each Tee							11 19
se two per each Cro	oss Fitting						1
Vasher Supports		Zinc Plated	HBTWS			1/	IXX
plices straight secti	ions and	Black	HBTWSBK				V V A
tings and can also	be used	Stainless Steel	HBTWSSS			2/	1 ~ /
a hold down meth							
ay to strut (nut and				· •	1	1	
ovided separately);					X	A YE	
50 pieces per box	vs	Zinc Plated	HBTUGS	A		1516	
50 pieces per box	və	ZING FIALEU	1003	(1)	1	A MA	
Self Tapping Screw			1	A DECEM		and the second	
Self Tapping Screw	orow and			the Annual Property of			
elf Tapping Screw vith Supports 4" - 20 self tapping s				7/25			
elf Tapping Screw				20		20	A A A
elf Tapping Screw ith Supports " - 20 self tapping s	ber box			70		->	17512

Dimensions in Inches (mm)

V-12