

Side Mount Designer Combination LED Unit

FEATURES

- Side mounted combo unit for commercial applications
- Optional LED based MR-16 lamps available for increased coverage and remote capacity
- High-impact, 5VA flame rated, UV stabilized, white thermoplastic housing
- Universal end/ceiling/wall mount and included canopy
- Fully adjustable, high output, MR16 halogen lamp heads
- Energy saving, long-life LED lamps exceed brightness and uniformity requirements
- Snap-in chevron arrows; 6" letters with 3/4" stroke
- Remote capacity with or without lamp heads
- Maintenance-free lead-acid battery with fully automatic charger
- Temperature range: 20°C to 30°C (68°F to 86°F)
- UL 924 Listed



EXIT SIGNS

ORDERING INFORMATION

HCX				-	
MODEL	FACES	LETTER COLOR	FINISH	OPTIONS	
	U Universal Single/ Double Face	R Red G Green	W White B Black	Blank	5W Halogen lamps
				03L	3W LED lamps
				RC12	12W Remote Capacity (includes lighting heads) ^{1,2}
				0-RC12	23W Remote Capacity (no lighting heads). Available in white only. ^{1,2}

¹RC12 and -0-RC12 options can be specified with the -03L option. Example HCXURW-0-RC12-03L

²No lamp-head option only available with remote capacity model

ACCESSORIES

MODEL	DESCRIPTION
WGTW	Wire guard (wall or ceiling mount)

MATCHING REMOTE HEADS

MATCHING 5W INDOOR REMOTE HEADS	
CPRSW0605	Single, White
CPRDW0605	Double, White
CPRSB0605	Single, Black
CPRDB0605	Double, Black
MATCHING 5W OUTDOOR REMOTE HEADS	
OCRSW0605	Single, White
OCRDW0605	Double, White
OCRSB0605	Single, Black
OCRDB0605	Double, Black
OCRSZ0605	Single, Dark Bronze
OCRDZ0605	Double, Dark Bronze

POWER CONSUMPTION

VOLTAGE	120VAC	277VAC
Red, Green	4.5W	4.5W

Power factor, average: .80 (lagging)
Wattage figures include LED lamps, transformers and electronics power requirements.

ELECTRONICS

- Transformer isolation, surge, transient, and low voltage disconnect protection
- Pre-stripped pigtail leads
- 90 minute emergency operation
- Reverse polarity, short circuit and AC lockout protection
- 120/277VAC 60Hz operation, test switch and LED AC-On indicator light

