


**FLEXIBLE METAL STRAIGHT SQUEEZE CONNECTORS****Straight Squeeze Connectors, Uninsulated Malleable Iron**
N/A**B61**

Catalog #: 2104-8

APPLICATIONSFor use in dry locations to bond flexible metal conduit to a box or enclosure
N/A**PRODUCT FEATURES**All malleable iron construction insures mechanical protection for the raceway
Electro zinc plated for added corrosion protection
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation**CULUS**

UL Listed E195969

GENERAL PRODUCT INFORMATION

Trade Size: 1 in.

DRAWING DIMENSIONSDimension A: 1-11/16 in.
Dimension B: 33/64 in.
Thread Spec. B: 1 in. - 11-1/2 NPT
Dimension C: .935 in.
Dimension D: 1.364 - 1.408
Dimension E: 2-25/64 in.**PACKAGING**Package Type: Carton
Std. Pkg.: 1
Ship Carton Qty.: 5
Product UPC-A Labeled: Yes
Weight (Lbs. Per/C): 31.30
Ship Carton Length (in.): 6.25
Ship Carton Width (in.): 4.50
Ship Carton Height (in.): 4.25
Ctn Weight (Lbs.): 1.57
UPC Number: 050169210482
I2of5: 50050169210487