



BURNDY Catalog Number
UPC Number
Description
Status

YA44LTC58FX
 7818100210711
 CU. COMP. TERM. - 750 MC
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	4.04
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.66
Barrel Type	Standard
Thickness	0.33
B Length (in)	1.65
Pad Width (in)	2.19
Strip Length	1-5/8

General

Number of Holes	1
Product Description	Copper Compression Lug, 1 Hole w/ Inspection Window, 777.7 Flex, 5/8" Stud, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range	750
Flex (Class H) Size - Range	750
Flex (Class I) Size - Range	750
Copper Solid Size (Range)	N/A
DLO Size (Range)	777.7 (1925/#24)
Copper Stranded (Range)	N/A

Physical

Type of Plating	Tin
Bolt Hole Size	5/8
Color Code	Yellow
Plated (Yes or No)	Y
Index Number	L115
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175