

Wire Basket Tray System

Electroplated Zinc Round Cross-Wire Basket Tray



Features

- T-weld construction prevents snags
- 5mm round wire minimum
- High load rating
- Easy to cut and fabricate fittings in the field
- 2" x 4" mesh opening
- Use factory support hardware or fabricate supports at the job site
- Electroplated zinc galvanized (post plated) made from carbon steel and plated to ASTM B 633, Type III, SC-1

Field Configurable Fittings




90° Sweep Elbow
Use appropriate quantity of splice kits




Tee Fitting
Use one HBTCS corner splice per each

Supports and Hardware



Ordering Information
See page V-12

Wire Diameter



.1969" Dia.
"Round" Wire Design

10 Feet per Length 118.3" (3m) 10 pc. min. order qty.	Tray Width	Load (Lb/ft)	Tray Weight per Length (Lb)	Splice Quantity*		Finish
				90° Sweep Elbow	Straight Splice	
2" Deep Tray	4" (102)	45	7	2	2	HBT0204ZP
	6" (152) ●	50	9	3	4	HBT0206ZP
	8" (203) ●	52	10.5	4	4	HBT0208ZP
	12" (305) ●	58	12	6	4	HBT0212ZP
	16" (406) ●	70	15	7	4	HBT0216ZP
	18" (457) ●	70	23	9	4	HBT0218ZP
	20" (508) ●	73	25	9	5	HBT0220ZP
	22" (559)	73	27	12	5	HBT0222ZP
	24" (610) ●	75	31	12	5	HBT0224ZP
	26" (660)	73	33	13	6	HBT0226ZP
	28" (711)	73	35	14	6	HBT0228ZP
	30" (762)	70	38	15	6	HBT0230ZP
	32" (813)	70	39	16	6	HBT0232ZP
4" Deep Tray	4" (102)	49	12	2	4	HBT0404ZP
	6" (152) ●	49	13	3	5	HBT0406ZP
	8" (203) ●	78	15	4	6	HBT0408ZP
	12" (305) ●	78	23	6	6	HBT0412ZP
	16" (406) ●	108	27	7	7	HBT0416ZP
	18" (457) ●	116	29	9	7	HBT0418ZP
	20" (508) ●	116	31	9	7	HBT0420ZP
	22" (559)	116	33	12	8	HBT0422ZP
6" Deep Tray	24" (610) ●	116	35	12	8	HBT0424ZP
	28" (711)	108	39	14	9	HBT0428ZP
	8" (203) ●	116	23	4	6	HBT0608ZP
	12" (305) ●	123	27	6	6	HBT0612ZP
	16" (406) ●	123	31	7	7	HBT0616ZP
	18" (457) ●	127	33	9	7	HBT0618ZP
	20" (508) ●	127	35	9	7	HBT0620ZP
	22" (559) ●	127	37	12	8	HBT0622ZP
8" Deep Tray	24" (610) ●	150	39	12	8	HBT0624ZP
	8" (203) ●	116	27	4	8	HBT0808ZP
	12" (305) ●	116	31	6	8	HBT0812ZP
	16" (406) ●	116	35	7	9	HBT0816ZP
	18" (457) ●	116	37	9	9	HBT0818ZP
	20" (508) ●	116	39	9	9	HBT0820ZP

Note: ●UL Classified/cUL Classified as equipment ground conductor.
All dimensions are +/- 0.25".

*See page V-13 for details and page V-14 for wire fill and maximum load chart.

Dimensions in Inches (mm)