





Wire Basket Tray System

Round Cross-Wire Basket Tray



Features

- T-weld construction prevents snags
- 5mm round wire minimum
- High load rating
- Easy to cut and fabricate fittings in the field
- 100% recycled steel
- 2" x 4" mesh opening
- Use factory support hardware or fabricate supports at the job site
- Painted tray includes factory installed masking to ensure proper grounding at splices; no need to remove paint during installation

10 Feet per Length 118.3" (3m) 10 pc. min. order qty. 2" Deep Tray	Tray Width	Load (Lb/ft)	Tray Weight per Length (Lb)	Splice Quantity*		Finish	
				90° Sweep Elbow	Straight Splice	Pre-Galvanized	Black Powder Coat
	4" (102)	45	7	2	2	HBTO204	HBTO204BK
	6" (152) ●	50	9	3	4	HBTO206	HBTO206BK
	8" (203) ●	52	10.5	4	4	HBTO208	HBTO208BK
	12" (305) ●	58	12	6	4	HBTO212	HBTO212BK
	16" (406) ●	70	15	7	4	HBTO216	HBTO216BK
	18" (457) ●	70	23	9	4	HBTO218	HBTO218BK
	20" (508) ●	73	25	9	5	HBTO220	HBTO220BK
	22" (559)	73	27	12	5	HBTO222	HBTO222BK
	24" (610) ●	75	31	12	5	HBTO224	HBTO224BK
	26" (660)	73	33	13	6	HBTO226	HBTO226BK
	28" (711)	73	35	14	6	HBTO228	HBTO228BK
	30" (762)	70	38	15	6	HBTO230	HBTO230BK
	32" (813)	70	39	16	6	HBTO232	HBTO232BK
	4" (102)	49	12	2	4	HBTO404	HBTO404BK
	6" (152) ●	49	13	3	5	HBTO406	HBTO406BK
	8" (203) ●	78	15	4	6	HBTO408	HBTO408BK
	12" (305) ●	78	23	6	6	HBTO412	HBTO412BK
	16" (406) ●	108	27	7	7	HBTO416	HBTO416BK
	18" (457) ●	116	29	9	7	HBTO418	HBTO418BK
	20" (508) ●	116	31	9	7	HBTO420	HBTO420BK
	22" (559)	116	33	12	8	HBTO422	HBTO422BK
	24" (610) ●	116	35	12	8	HBTO424	HBTO424BK
	28" (711)	108	39	14	9	HBTO428	HBTO428BK
	8" (203) ●	116	23	4	6	HBTO608	HBTO608BK
	12" (305) ●	123	27	6	6	HBTO612	HBTO612BK
	16" (406) ●	123	31	7	7	HBTO616	HBTO616BK
	18" (457) ●	127	33	9	7	HBTO618	HBTO618BK
	20" (508) ●	127	35	9	7	HBTO620	HBTO620BK
	22" (559) ●	127	37	12	8	HBTO622	HBTO622BK
	24" (610) ●	150	39	12	8	HBTO624	HBTO624BK
	8" (203) ●	116	27	4	8	HBTO808	HBTO808BK
	12" (305) ●	116	31	6	8	HBTO812	HBTO812BK
	16" (406) ●	116	35	7	9	HBTO816	HBTO816BK
	18" (457) ●	116	37	9	9	HBTO818	HBTO818BK
	20" (508) ●	116	39	9	9	HBTO820	HBTO820BK

Note: ●UL Classified as equipment ground conductor (painted tray cUL Classified only).

All dimensions are +/- 0.25". Custom paint colors available in addition to Black Powder Coat (Contact Hubbell).

*See page V-13 for details and page V-14 for wire fill and maximum load chart.

HBTO202 (2x2 tray) available as special order. MOQ 40 pcs. Top wire utilizes side weld.

Field Configurable Fittings



90° Sweep Elbow


Use appropriate quantity of splice kits



Tee Fitting

Use one HBTC corner splice per each


Supports and Hardware



Ordering Information

See page V-12

Wire Diameter



.1969" Dia.
"Round" Wire Design

Dimensions in Inches (mm)