




## EMT SET SCREW CONNECTORS

Uninsulated Set Screw Connector, Steel

B03



Catalog #: 2144US

### APPLICATIONS

For use in dry locations to bond EMT conduit to a box or enclosure. RACO steel set screw connectors provide concrete-tight connections when taped.  
For use in dry locations to bond unthreaded rigid/IMC conduit to a box or enclosure. RACO steel set screw connectors provide concrete-tight connections when taped.

### PRODUCT FEATURES

All steel construction ensures mechanical protection for the raceway  
Tri-head screws may be installed using a slotted, Phillips, or Robertson head screwdriver  
2-1/2 in. to 4 in. trade sizes are also UL listed for use on EMT or Rigid/IMC conduit, allowing for design and installation flexibility  
All components are zinc electroplated for corrosion protection  
1/2 in. to 1 in. trade sizes have one set screw, 1-1/4 in. to 4 in. trade sizes have two set screws  
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation

### UL LISTED

2-1/2" - 4" Standard 514B, File E195969, E195970  
Standard 514B, UL Listed E195969

### CULUS

1/2" - 2" Standard 514B, C22.2 # 18

### COMPLIANCES

MSDS  
[www.hubbell-rtb.com/certifications/Hubbell-RACO\\_MSDS\\_for\\_WP\\_Boxes\\_and\\_Fittings.January\\_2015.pdf](http://www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings.January_2015.pdf)

### GENERAL PRODUCT INFORMATION

Sub Class: Uninsulated  
Trade Size: 3-1/2 in.

### DRAWING DIMENSIONS

Dimension A: 3.46 in.  
Dimension B: 4.06 in.  
Dimension D: .717 in.  
Dimension E: 1/4 - 28

### PACKAGING

Package Type: Carton  
Ship Carton Qty.: 1  
Product UPC-A Labeled: No  
Weight (Lbs. Per/C): 250.00  
Ship Carton Length (in.): 5.50  
Ship Carton Width (in.): 5.50  
Ship Carton Height (in.): 4.19  
Pallet Qty: 280  
UPC Number: 050169570203