

5" SHALLOW CEILINGS

HOUSINGS & TRIMS

For complete fixture, order housing with trim.

Shallow IC and Non-IC Universal Housings

New Construction

Air-Tight IC and Non-IC



P84-AT

Ceiling opening: 5-1/4"
Plaster frame: 7-7/8" x 10-3/4"
Recessed depth: 5-1/4"
Pryouts: 1/2" & 3/4"

P84-AT

- Notched mounting frame for easy alignment
- Can be installed in ceilings from 1/2" to 1-1/2" thick
- Nail grip bar hangers accommodate up to 24" on center ceiling joists
- Slotted interlocking bar hangers provide solid mounting on 24" centers
- Locking feature to secure housing
- Integral T-bar clamps
- Integral Romex clamps
- UL & CUL listed for damp locations & through wiring
- Rated for 8 #12 90° conductors (4 in/4 out)
- Trims are easy-in & push-lock into place
- Shallow profile (5-1/2") for 2x6 construction
- Adjustable lamp position
- Meets Washington State Energy Code requirements

Shallow Remodel IC and Non-IC



P184-TG

Ceiling opening: 5-1/8"
Recessed depth: 5-1/2"
Pryouts: 1/2"

P184-TG

- Locking clips (furnished) permit quick mounting in ceiling
- Can be installed in ceilings from 1/2" to 1" thick.
- UL & CUL listed for damp locations
- Rated for 4 #12 90° conductors (2 in/2 out).
- Rated for 60° supply wires in end-of-run applications.
- Trims are easy-in & push-lock into place
- Shallow profile (5-1/2") for 2x6 construction

IC/Non-IC Trims

For insulated and non-insulated ceilings. 6-1/8" outside diameter. IC/Non-IC applications.



SHALLOW BAFFLE

P8375-28 White
P8375-31 Black
65w BR-30, 50w PAR-30



OPEN

P8368-28 White
65w BR-30, 50w PAR-30



ALZAK®

P8368-21A Clear Alzak®
65w BR-30, 50w PAR-30



ALZAK®

P8368-22A Gold Alzak®
65w BR-30, 50w PAR-30



EYEBALL

P8176-28 White
6-3/8"
75w PAR-30 Short Neck



DROP OPAL SHOWER

P8109-28 White
Wet location listed
Metal flange
30w R-20



OPEN SHOWER TRIM

P8367-WL28 White
Wet location listed
50w PAR 30*

(Image: Kolter Holmes)