

## LED Three-Head White AC Track Kit

Ceiling mounted • Dry location listed



### Description:

Ideal for residential and light commercial applications, this LED Track Kit is ready to install. Track Kits include 42" of linear track, a floating power feed, three large AC LED Track Heads and installation hardware. Track Heads feature a frosted glass lens to reduce glare and are compatible with P9054 and P9058 track and accessories.

### Specifications:

- Satin White (-028) (painted)
- Die Cast Aluminum construction
- Frosted glass lens
- 120V AC LED Track
- Ideal for residential and light commercial applications
- Track Kits include 42" of linear track, a floating power feed, three large AC LED Track Heads and installation hardware
- Track Heads feature a frosted glass lens to reduce glare and are compatible with P9054 and P9058 track and accessories
- Satin White Finish
- Track is 42" length and 2-3/4in ht., Track head measures 2-7/8in w and 6-1/2in ht.
- Each tack head has one 9.5w LED with 533 lumens, 90+ CRI and 2700K
- LED Track Kit is ready to install
- Flicker free dimming down to 10% with many Triac or reverse phase dimmers
- ENERGY STAR and JA8 Title 24 compliant
- Additional track heads available P900000-028-27
- Dimmable to 10% brightness (See Dimming Notes)
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

### Performance:

|                        |                                    |
|------------------------|------------------------------------|
| Number of Modules      | 3                                  |
| Input Power            | 9.5w per module                    |
| Input Voltage          | 120 V                              |
| Input Frequency        | 60 Hz                              |
| Lumens/LPW (Source)    |                                    |
| Lumens/LPW (Delivered) | 1575/55 (LM-79) per module         |
| CCT                    | 2700 K                             |
| CRI                    | 90+ CRI                            |
| Life (hours)           | 50,000 (L70/TM-21)                 |
| FCC                    |                                    |
| Min. Start Temp        | -30 °C                             |
| Max. Operating Temp    | 30 °C                              |
| Warranty               | 5 year warranty                    |
| Labels                 | cETLus Dry location listed         |
|                        | ENERGY STAR® qualified             |
|                        | Meets California Title 24 JA8-2016 |

**P900002-028-27**

### Images:



### Dimensions:

Width: 2-7/8"  
 Depth: 2-3/4"  
 Length: 42"  
 Height: 6-1/2"

## LED Three-Head White AC Track Kit

Ceiling mounted • Dry location listed



**P900002-028-27**

### Dimming Notes:

---

P900002 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

### Dimming Controls

---

Lutron NTELV-300

Lutron Caseta

Lutron AY-600P

Lutron LG-603PG

Leviton 6672

Leviton 6674

Lutron AYCL-153P

Lutron DVCL-153P

Lutron MACL-153M

Lutron AYL-600P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.