

# WISH

Wall mounted • Wet location listed



## Description:

LED wall lantern with etched umber linen glass. Includes dark sky shield for full cut-off illumination or remove for a traditional lighting effect. 120V AC replaceable LED module, 623 lumens, 3000K color temperature and 90+ CRI.

## Specifications:

Antique Bronze (-20) (powdercoat)  
 Aluminum construction  
 Etched UMBER LINEN glass cylindrical diffuser  
 Dimmable (See Dimming Notes)  
 Back plate covers a standard 4" hexagonal recessed outlet box  
 Mounting strap for outlet box included  
 6" of wire supplied  
 ENERGY STAR® qualified

## Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	623/69.2 (LM-79)
CCT	3000 K
CRI	90
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified

## P6084-2030K9

## Images:



## Dimensions:

Width: 7"  
 Height: 10-3/8"  
 Depth: 8-5/8"  
 H/CTR: 3-1/8" (facing up)

Glass  
 Width: 4-5/8"  
 Height: 5-7/8"

**P6084-2030K9****Dimming Notes:**

---

P6084-2030K9 is designed to be compatible with many Electronic Low Voltage (ELV/Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Vienti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.  
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.