

# One-Light Pendant

Ceiling stem hung with 6 links of chain • Damp location listed



## Description:

The One-Light LED mini-pendant features industrial roots in both form and function. The Oil Rubbed Bronze finish highlight the high-quality prismatic glass which adds to the historical aesthetic. Perfect above a kitchen island in pairs or threes, use for additional ambience or task lighting in a bathroom, bedroom or anywhere a pendant light can be placed. 3000k, 90+ CRI 623 lumens.

## Specifications:

- Oil Rubbed Bronze (-108) (painted)
- Steel Construction
- Clear Fresnel glass lens
- LED Module is replaceable (part # 93054049)
- Oil Rubbed Bronze finish.
- Fresnel glass lens.
- Antique inspired with industrial roots
- Includes one 6", four 12" stems and 6 links of chain.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied
- One 6", four 12" lengths of stem included
- Six links of 9 gauge chain supplied
- ENERGY STAR® qualified

## Performance:

|                        |                                     |
|------------------------|-------------------------------------|
| Number of Modules      | 1                                   |
| Input Power            | 9w                                  |
| Input Voltage          | 120 V                               |
| Input Frequency        | 60 Hz                               |
| Lumens/LPW (Source)    | 623/69.2 (LM-82)                    |
| Lumens/LPW (Delivered) | 521/66.8 (LM-79)                    |
| CCT                    | 3000 K                              |
| CRI                    | 90 CRI                              |
| Life (hours)           | 60,000 (L70/TM-21)                  |
| FCC                    | Meets FCC Title 47, Part 15 Class B |
| Min. Start Temp        | -30 °C                              |
| Max. Operating Temp    | 30 °C                               |
| Warranty               | 5 year warranty                     |
| Labels                 | cCSAus Damp location listed         |
|                        | ENERGY STAR® qualified              |

## P5050-10830K9

## Images:



## Dimensions:

Diameter: 6-1/8"  
 Height: 6-1/4"  
 Overall Ht. W/Stem: 72-1/4"

Glass  
 Width: 5-3/8"  
 Length: 5-3/8"  
 Height: 0-1/2"

# One-Light Pendant

Ceiling stem hung with 6 links of chain • Damp location listed



## P5050-10830K9

### Dimming Notes:

P5050 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

### Dimming Controls

|         |               |            |
|---------|---------------|------------|
| Lutron  | Nova T        | NTELV-300  |
| Lutron  | Vierti        | VTELV-600  |
| Lutron  | Ariadni       | AYCL-153P  |
| Lutron  | Diva          | DVCL-153P  |
| Lutron  | Maestro       | MAELV-600  |
| Lutron  | spacer/system | SPSELV-600 |
| Leviton | Renoir II     | AWRMG-EAW  |

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.