

# 5" LED

## 5" LED HOUSING NEW CONSTRUCTION

For complete fixture, order housing with trim.

Air-Tight IC



### P84-LED

Ceiling opening: 5-1/4"  
Plaster frame: 7-7/8" x 10-3/4"  
Recessed depth: 5-1/2"  
Pryouts: 1/2" & 3/4"

- Integral quick connectors mate with P8061 and P8176 series

## 5" LED TRIM - TRIAC DIMMING

Flicker free dimming down to 10% with many Triac or forward phase dimmers.  
Flicker rate less than 30%.

**P8061-09-30K** Brushed Nickel  
**P8061-20-30K** Antique Bronze  
**P8061-28-30K** White  
**P8061-31-30K** Black  
One 10.5w LED module included.  
700 lumens, 66 lumens per watt.



P8061-09-30K



P8061-20-30K



P8061-28-30K



P8061-31-30K

### P8061 & P8176 FEATURES

- Frosted polycarbonate lens controls direct glare from LEDs
- Lumen output and distribution comparable to 65w BR30 incandescent lamp
- CRI is 90+ rivaling CFL
- 50,000 hours life based on 70% lumen maintenance (TM-21)
- Suitable for use in IC or NON-IC applications
- Can also be used with P85-AT, P85-TG and P185-TG
- cULus listed for wet locations

## 5" LED TRIM - ELV DIMMING

Flicker free dimming down to 10% with many ELV dimmers.

**P8061-20/30K9-AC-L06** Antique Bronze  
**P8061-28/30K9-AC-L06** White  
**P8061-31/30K9-AC-L06** Black  
**P8061-82/30K9-AC-L06** Metallic Gray  
One 12w LED module included.  
670 lumens, 55 lumens per watt.



P8061-20/30K9-AC-L06



P8061-28/30K9-AC-L06



P8061-31/30K9-AC-L06



P8061-82/30K9-AC-L06



*Includes Edison base socket and Quick-Link connector*

## 5" EYE BALL - TRIAC DIMMING

Flicker free dimming down to 10% with many Triac or forward phase dimmers.  
Flicker rate less than 30%.

**P8176-09-30K** Brushed Nickel  
**P8176-20-30K** Antique Bronze  
**P8176-28-30K** White  
**P8176-31-30K** Black  
One 10.5w LED module included.  
670 lumens, 63 lumens per watt.



P8176-09-30K



P8176-20-30K



P8176-28-30K



P8176-31-30K