

6" INCANDESCENT

IC, NON-IC, AIR-TIGHT UNIVERSAL HOUSINGS

For complete fixture, order housing with trim.

New Construction
Air-Tight IC and Non-IC



P87-AT
Ceiling opening: 6-7/8" dia.
Plaster frame: 7-7/8" x 10-3/4"
Recessed depth: 7-1/4"
Pryouts: 1/2" & 3/4"

- P87-AT**
- Can be installed in ceilings from 1/2" to 2-1/2" thick
- Meets Washington State Energy Code requirements
- UL & CUL listed for damp locations and through wiring
- Integral Romex clamp
- Tool-less can adjustment for varying ceiling thickness
- Slotted, interlocking bar hangers securely span 24" T-bar spacing
- Full reflector design eliminates light leaks
- Rated for 8 #12 90° conductors (4 in/4 out)
- US Patent #5758959, 5857766, 6004011

New Construction
Air-Tight IC and Non-IC



P87-ATQC
Ceiling opening: 6-7/8" dia.
Plaster frame: 7-7/8" x 10-3/4"
Recessed depth: 7-1/4"
Pryouts: 1/2" & 3/4"

- P87-ATQC**
- Quick-connects allow simple installation of 12-20 AWG wire, without the need for wire nuts
- Can be installed in ceilings from 1/2" to 2-1/2" thick
- Meets Washington State Energy Code requirements
- UL & CUL listed for damp locations and through wiring
- Integral Romex clamp
- Tool-less can adjustment for varying ceiling thickness
- Slotted, interlocking bar hangers securely span 24" T-bar spacing
- Full reflector design eliminates light leaks
- Rated for 8 #12 90° conductors (4 in/4 out)
- US Patent #5758959, 5857766, 6004011

Remodel IC and Non-IC



P187-TG
Ceiling opening: 6-5/8" dia.
Recessed depth: 7-1/2"
Pryouts: 1/2"

- P187-TG**
- Retrofit version of the P87-AT
- Exclusive mounting slide bars permit quick and solid mounting in ceilings
- Can be installed in ceilings from 1/2" to 1-1/2" thick
- IC/Non-IC peel away label for field conversion
- UL and CUL listed for damp locations and through wiring
- Rated for 4 #12 90° conductors (2 in/2 out)
- Rated for 60° supply wires in end-of-run applications
- Can be converted to Air-Tight in the field with the P8593-01 gasket kit.
- US Patent #5758959

For insulated or non-insulated ceilings. 7-3/4" outside diameter (OD), except where indicated.



Quick-connect

NON-IC TRIMS

Insulation must be 3" from housing. 7-3/4" outside dia.



PIN HOLE
P8065-28 White with Black Baffle
75w PAR16, 40w R16, 50w R20/PAR20/PAR30, 40w A19

WALL WASHER
P8052-28 White Baffle
60w A19

FRESNEL
Wet location listed
P8062-28 White
Metal flange
60w A19, 75w PAR 30 Short Neck

ALBALITE GLASS
Wet location listed
P8060-28 White
Metal flange
60w A19, 75w PAR 30 Short Neck

ALBALITE GLASS
Wet location listed
P8008-60 White
Non-metallic flange
60w A19, 75w PAR 30 Short Neck

IC TRIMS & NON-IC TRIMS



STEP BAFFLE
P8066-28 White
75w PAR 30, 65w BR30
150w PAR 38, 120w BR40, 40w A19

STEP BAFFLE
P8066-09 Brushed Nickel
Unpainted flange
75w PAR 30, 65w BR30
150w PAR 38, 120w BR40, 40w A19

STEP BAFFLE
P8066-20 Antique Bronze
Unpainted flange
75w PAR 30, 65w BR30
150w PAR 38, 120w BR40, 40w A19

STEP BAFFLE
P8066-31 Black
White flange
75w PAR 30, 65w BR30
150w PAR 38, 120w BR40, 40w A19

STEP BAFFLE
P8082-31 Black
P8082-28 White
8-3/4"
90w PAR 38, BR40
150w PAR38, 150w BR40

LONG NECK BAFFLE
P8075-28 White
P8075-31 Black
65w BR30
75w PAR30 long neck
100w A19, 75w PAR 30 Long Neck, 85w BR 30



EYEBALL
Rotates 358°, tilts 30° max.
P8076-20 Antique Bronze
75w PAR 30, 65w BR30



EYEBALL
Rotates 358°, tilts 30° max.
P8076-09 Brushed Nickel
P8076-28 White
75w PAR 30, 65w BR30



BAFFLED MINI EYEBALL
Rotates 358°, tilts 30° max.
P8077-28 White Baffle
75w R20, PAR 20



REGRESSED BAFFLED EYEBALL
Rotates 358°, tilts 30° max.
P8079-28 White Baffle
65w BR30, 50w PAR 30
75w PAR 30, 85w BR 30



REGRESSED BAFFLED EYEBALL
Rotates 358°, tilts 30° max.
P8079-31 Black Baffle
65w BR30, 50w PAR 30
75w PAR 30, 85w BR 30



REGRESSED MINI EYEBALL
Rotates 358°, tilts 30° max.
P8078-28 White
75w R 20, PAR 20



OPEN
P8074-28 White
8-3/4"
90w BR40/PAR 38
150w PAR 38, 120w BR40



OPEN SPLAY
P8072-28 White
75w PAR 30 Long Neck, 65w BR 30
75w PAR30 Long Neck, 100w A19, 85w BR 30



CONES
P8068-21A Clear Alzak®
White flange
75w PAR 30, 65w BR30
150w PAR 38, 120w BR 40, 40w A19



CONES
P8068-28 White
White flange
75w PAR 30, 65w BR30
150w PAR 38, 120w BR 40, 40w A19



CONES
P8068-22A Gold Alzak®
White flange
75w PAR 30, 65w BR30
150w PAR 38, 120w BR 40, 40w A19



CONES
P8053-31 Black Alzak®
Black flange
75w PAR 30, 65w BR30
150w PAR 38, 120w BR 40, 40w A19



DROP OPAL SHOWER
Wet location listed
P8007-60 White
Metal flange
8-1/4"
60w A19, 50w PAR30
100w A19, 75w PAR 30



DROP OPAL SHOWER
Wet location listed
P8009-60 White Glass
Non-metallic flange
40w A19, 50w PAR 30
75w A19, 75w PAR 30



DOME SHOWER
Wet location listed
P8025-60 White
Polycarbonate
8-3/4"
40w A19
75w A19



OPEN SHOWER
Wet location listed
P8072WL-28* White
Metal flange
50w PAR 30 Long Neck



OPEN SHOWER
Wet location listed
P8074WL-28 White
Metal flange
75w PAR 38*



FRESNEL SHOWER
Wet location listed
P8011-60 White
Non-metallic flange
50w PAR 30 SN
75w PAR 30 Short Neck

For insulated or non-insulated ceilings. 7-3/4" outside diameter (OD), except where indicated.

** WL trims require use with outdoor rated PAR lamps*