

6" LED

6" LED HOUSING NEW CONSTRUCTION AND REMODEL

For complete fixture, order housing with trim.

New Construction
Air-Tight IC and Non-IC



P87-LED
Ceiling opening: 6-7/8" dia.
Plaster frame: 7-7/8" x 10-3/4"
Recessed depth: 7-1/2"
Pryouts: 1/2" & 3/4"

- Integral quick connect mates with P8071 and P8076 series LED trims.

6" LED TRIM 800 LUMENS - ELV DIMMING

Flicker free dimming down to 10% with many ELV dimmers.

P8071-20/30K9-AC1-L08 Antique Bronze
P8071-28/30K9-AC1-L08 White
P8071-31/30K9-AC1-L08 Black
P8071-82/30K9-AC1-L08 Metallic Gray



Includes Edison base socket and Quick-Link connector



P8071-20/30K9-AC1-L08



P8071-28/30K9-AC1-L08



P8071-31/30K9-AC1-L08



P8071-82/30K9-AC1-L08

FEATURES

- Frosted polycarbonate lens controls direct glare from the LEDs
- Flicker-free dimming with many ELV dimmers (see progresslighting.com)
- 13-watt input power
- Lumen output 825 lumens
- Lumen output and distribution comparable to a 65w BR30 incandescent lamp
- CRI is 90+ rivaling CFL
- 50,000 hours life based on 70% lumen maintenance (TM-21)
- Suitable for use in IC or NON-IC applications
- Can also be used with P86-TG, P87-AT, P87-ATQC, P186-TG, P187-TG
- CSAus listed for wet locations

6" LED TRIM 1000 LUMENS - TRIAC DIMMING

Flicker free dimming down to 10% with many Triac or forward phase dimmers. Flicker rate less than 30%.

P8071-2830K-L10-STR2 White
1000 lumen 3000K

P8071-2835K-L10-STR2 White
1000 lumen 3500K



Includes Edison base socket and Quick-Link connector



P8071-2830K-L10-STR2



P8071-2835K-L10-STR2

FEATURES

- Frosted polycarbonate lens controls direct glare from the LEDs
- Dimmable to 10%
- 12-watt input power
- Lumen output 1037 lumens
- Lumen output and distribution comparable to a 75w PAR30 incandescent lamp
- CRI is 80+ rivaling CFL
- 60,000 hours life based on 70% lumen maintenance (TM-21)
- Suitable for use in IC or NON-IC applications
- Available in 3000K and 3500K color temperatures
- cULus listed for wet locations

6" LED TRIM - ELV DIMMING

Dimmable down to 10% with many ELV type dimmers.

P8071-2030K9-AC1-L07 Brushed Nickel
P8071-2830K9-AC1-L07 White
P8071-3130K9-AC1-L07 Black
P8071-8230K9-AC1-L07 Metallic Gray
One 12w LED module included.
717 lumens, 59 lumens per watt.



P8071-2030K9-AC1-L07



P8071-2830K9-AC1-L07



P8071-3130K9-AC1-L07



P8071-8230K9-AC1-L07

P8071 & P8076 FEATURES

- Frosted polycarbonate lens controls direct glare from the LEDs
- Lumen output and distribution comparable to a 65w BR30 incandescent lamp
- 3000K color temperature
- 90+ CRI
- TM-21 60,000 hours life
- Suitable for use in IC or NON-IC applications
- CSAus listed for wet locations

6" LED TRIM - TRIAC DIMMING

Flicker free dimming with Triac or forward phase dimmers. Flicker rate less than 30%.

P8071-09-30K Brushed Nickel
P8071-20-30K Antique Bronze
P8071-28-30K White
P8071-31-30K Black
One 10.5w LED module included.
725 lumens, 69 lumens per watt.



P8071-20-30K



P8071-28-30K



P8071-31-30K



P8071-09-30K

6" EYE BALL - TRIAC DIMMING

Flicker free dimming down to 10% with many Triac or forward phase dimmers. Flicker rate less than 30%.

P8076-09-30K Brushed Nickel
P8076-20-30K Antique Bronze
P8076-28-30K White
P8076-31-30K Black
One 10.5w LED module included.
700 lumens, 66 lumens per watt.



P8076-09-30K



P8076-20-30K



P8076-28-30K



P8076-31-30K